

STATE OF MICHIGAN
 COUNTY OF BARRY
 RECEIVED FOR RECORD

DEC 9 3 02 PM '93

Sandy Schindelmaier
 REGISTER OF DEEDS

002145

Register of Deeds Stamp & File Number

Barry County Remonumentation
 LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

corners in

Barry County
 (County)

Located In: Irving Twp. Corner Code # G-4

Public Land Survey

T 4N R 9W

Property Controlling
 in Section
 Miscellaneous
 Property in Sec.

S T R
 S T R
 S T R
 S T R

Lot No. _____, Recorded Plat _____
 Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Robert Jonker in a field survey on Feb. 18, 1993, hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

No info on record @ County Surveyor Office
 No info on record at Road Commission.

LCRC #471, 1993, JONKER, Gear spike.

Spike on E. side 16" Box Elder S15°W 54.43'
 Spike on W. side 16" Box Elder S10°E 61.82'
 Spike on S. side 30" Oak N65°W 59.03'
 Iron N 33'

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found corner as recorded in #471, 1993, as listed in "A" above.

And is accepted as the best available evidence of the position of the original corner.

SURVEY &
 REMONUMENTATION


APR 05 1994

COMMISSION

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced with 3/4"x36" std. capped Barry County Monument.

Spike on E. side 16" Box Elder S15°W 54.43'
 Spike on W. side 16" Box Elder S10°E 61.82'
 Spike on S. side 30" Oak N65°W 59.03'
 Iron N. 33'



signed by Robert J. Jonker Date 11/29/93
 Surveyor's Michigan License No. #21572