

STATE OF MICHIGAN
 COUNTY OF BARRY
 RECEIVED FOR RECORD

DEC 9 3 02 PM '93

Barry County Remonumentation
 LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

Sandy Schondelmaier
 REGISTER OF DEEDS

002147

Register of Deeds Stamp & File Number

For corners in

Barry County
 (County)

Located In: Irving Twp. Corner Code #/

Public Land Survey	T 4N R 9W	T-3
	T R	
	T R	
	T R	
Property Controlling in Section	S T R	
	S T R	
Miscellaneous Property in Sec.	S T R	
	S T R	

Lot No. _____ Recorded Plat _____
 Private Claims _____

Robert Jonker in a field survey on Feb. 18, 1993

I hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Description of original monument and accessories and/or subsequent restoration:
 Recorded in 1993, Jonker, LCRC #472, rerod.

- Nail-W.side 22' Beech, S40°E 18.2'
- Nail-S.side 24" tree S75°W 25.73'
- Nail-S.side 26" Poplar N85°E 16.6'
- Nail-W.side 16" Poplar N25°E 22.63'

Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 Found corner per witnesses listed in "A" above per LCRC #472

And is accepted as the best available evidence of the position of the original corner.

SURVEY &
 REMONUMENTATION
 APR 05 1994
 COMMISSION

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- Replaced with 3/4"x36" Std. capped Barry County Monuments.
- Nail-S.side 22" Beech S.40°E 18.2'
- Nail-S.side 24" tree S75°W 25.73'
- Nail-S.side 26" Poplar N85°E 16.6'
- Nail-W.side 16" Poplar N25°E 22.63'

N-S fence is 0.8'E
 E-W fence is 018'S



Robert J. Jonker

Surveyed by Robert J. Jonker Date 11/29/93
 Surveyor's Michigan License No. #21572