B YEMBUC ENGLISH AND SELECT SON THE SALES CHARLES

MAY 2 0 1997

AFARRICKON:

For corners in

Barry County

in Section

Property in Sec.

3. Miscellaneous

4. Lot No. 5. Private Claims _

expressed below:

(County)

BARRY COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Corner Code ##

STATE OF MICHIGAN COUNT FORY RECE ; pr

DEC 10 11 57 AM '96

Sandy Buch	i. Lilmaye
REGISTER	OF DEEDS

Register of Deeds Stamp & File Number

129W

10 11

12

40 RION

Irving Twp. A-1 T 4N R 9W 1. Public Land Survey Cor. Sec.6 SAME AS TAN A TOW T _____ R ____ 2. Property Controlling ____ T ____ R ____. S _____ T ____ R ____. S ____ T ___ R __ ... __ T ____ R

Located in:

I. Robert Jonker, in a field survey on __ _November 29 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as

___, Recorded Plat _____

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K.C. LCRC #1131, 1978, MVK
Spike in W side 28" Oak S-SE 131.55' Spike in SW side 26" Mulberry NW 33.46' PK in SE side P & T Pole NE 36.88'

-see over-

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Took witnesses in Spring of 1996 prior to road construction, reset position Fall of 1996 from construction witness and survey of parcel to the South in Barry Co.

Set Std. K.C. Mon. (Harrison)

Accepted as the best available evidence of the position of the corner.

ACT 345 BARRY COUNTY REMONUMENTATION

APPROVED BY PEER REVIEW AT A MEETING HELD ON

12-6-94 **BRIAN REYNOLDS**

COUNTY SURVEYOR

ROBERT J.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A NOW

Kent Co. Mon. (Harrison)

Kent Co. Remon nail & tag on NW side P.Pole Kent Co. Remon nail & tag on N side G.Pole

Kent Co. Remon nail & tag in SE side P.Pole

C/L base of street sign post

Top of NW cor. steel guard rail post

@ C/L "X"

S60°W 56.52' N33°W 39.10' N44°E 36.90'

S63°E 48.31

S19°W 63.24'

PROFESSION NO. 21572

Surveyor's Michigan License No


Date <u>December 2, 1996</u>

2455 - A

```
K.C. LCRC #1715, 1981, W&W, K.C. Mon.

Nail & remon tag in SW side 24" Mulberry
Nail & remon tag in W side 31" Oak
Nail & remon tag in SE side 18" Pear
Nail & remon tag in S side 6" Maple
Nail & remon tag in E side 27" Mulberry
Nail & remon tag in W side 8" Cedar
Nail & remon tag in N side 12" Maple
Set Mon. 3" under surface of gravel road N-S & E-W
```

```
K.C. LCRC #7002, 1994, Wm. Byl
Nail & remon tag SW side 32" Mulberry
Nail & remon tag W side 31" Oak stump
Nail & remon tag S side 12" Maple
Nail & remon tag E side 30" Mulberry
Nail & remon tag W side 12" Cedar
Nail & remon tag N side 18" Maple
N40°E 40.75'
Nail & remon tag N side 18" Maple
```



Part A Con't.

MAY 2 n 1997

COMPACE WAR