

SURVEY & REMONUMENTATION

MAR 31 1994

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970  
BAY COUNTY REMONUMENTATION PROJECT - 1993

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 13 N. S., R. 6 E. W.	L-13
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ N. S., R. _____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. S., R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

LIBER 003 PAGE 67  
 REGISTER OF DEEDS  
 BAY COUNTY, MICHIGAN  
 REGISTER OF DEEDS STAMP AND FILING NUMBER  
 JAN 27 1 46 PM 1994  
 RECORDED


I, Duane F. Ledy, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on DECEMBER 27, 1993, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:  
 J. Wampler set post in 1821 at 40.00 chains West of M-13.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  
 No corner found, no surveys or L.C.R.C. of record indicating corner was found or established. Set corner at mid-point on line between K-13 and M-13, per location approved by Bay County Peer Review Group and corner ratified on November 24, 1993.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" rod with Bay County brass cap (set approximately 20" deep)  
 North - ' 1/2" w/21575 cap set on Field Line  
 South - ' 1/2" w/21575 cap set on Field Line  
 West - 329.74' 1" x 1/2" Bar set by C.P.Co. in 1972  
 East - 2633.96'



SIGNED BY Duane F. Ledy DATE January 13, 1994  
 SURVEYOR'S MICHIGAN REGISTRATION NO. 21575 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
 CHIEF OF SURVEY PARTY  
 APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
 MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_