LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF –:	LOCATED IN –:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 25 N. S., R. 13 E. W.	K-9;K-8; M-8;M-9
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 21, 19 80, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B: Continued

M-8 Fd 1 1/2" pipe for E 1/4 Cor. Sec.24. Pipe is at SE Corner of Cor.fn. Post, fn N&W. Corner fits F. Haswell Sec.24, sub'n.,Feb.1894, Liber "O", Pg.136.

K-8 Re-established W 1/4 Cor.Sec.24 on line across fd ctr.& E 1/4 Cor & at Rec. Haswell dist. from Ctr. Sec.24. Corner falls in E-W fn line (wire in trees). See F. Haswell Sec.24 Subn., Feb. 1894, Liber "O", Pg. 136.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-9 Re-established SW Cor. of Sec.24 at average of Lat.&Dep. by double across the fd 1/4 Corners & 1/8 Corners 1/4 mile & 1/2 mile to West & to South. This fits Haswell tie N.to W.1/4 S-24 within - 3'; fits Langford tie S. to W 1/4 S-25 within - 7', fits Pettitt tie W. to N.1/4 S-26 exactly & fits Haswell tie E. to S 1/4 S-24 within-14'. See: S-24 F.S. Haswell 1894 Sur. Liber "O", Pg.136; S-25 G. Langford 1900± Sur. Liber "O" Pg.46; S-26 J.A. Pettitt 1900± Sur., Liber "O", Pg.134.

M-9 Fd & accepted 1" pipe for SE Cor. of Sec.24. Ctr of N-S gravel rd. in curve is 10'± West. Corner fits RLS, Jack Gavin distance West to S 1/4 of Sec.24.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-9

Set DNR Mon & Ced. Post

11"	R. Pine	N30°W	5.4
3"	R. Pine	S60°E	14.5
8"	Maple	S82°E	37.6
7"	Oak	S20°E	53.5

E-W fn remains (Partially down) South 45'±

M-9

Fd. 1"x24" Pipe

10"	R. Pine	S10°E	92.47
8"	Maple	S62°W	48.82
Fd.sq.Conc.Mon		N85°W	60.02
4"	Maple	N70°W	67.70

M-8

Fd 1 1/2"x4 1/2' Pipe & Lg Stone & set Ced. Post W/loc tag

12"	Maple	N10°W	2.83
13"	Maple	S70°E	24.82
9"	Triple Maple	S45°W	30.03

K-8

Set DNR Mon & Ced Post

12"	Cherry	N78°W	65.4
9"	Maple	N15°W	38.9
10"	Twin Maple	N30°E	20.2

SIGNED BY Carl F. Roser 3-31-81 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

STATE OF MICHIGAN (SEAL) CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Colfax Township
BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET