LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	LOCATED IN-:	CORNER CODE NUMBER	,
1. PUBLIC LAND SURVEY	т. <u>25</u> ., к. <u>13</u>	D-1; D-2	
2. PROPERTY CONTROLL- 5 ING IN SECTION—5	, _T . 25 N. R. 13 w	5	
3. MISCELLANEOUS PROPERTY IN SECTION	_ ,T N. S., R W		
4. LOT NO, RECO	ORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in li re-established, monumented, re- and rules therefore as required i Bureau of Land Management or and 5 above were, in a field surve	nes 1 and 2 above were, in monumented, recovered or in the current manual of sur by a decree of a court of largy on	a field survey on November restored as expressed below and every instructions of the United Sw. Furthermore, that the corne, 19, found, recovered, res	of P.A. 74, Michigan P.A. of 1970, 13, 1980, established. If in conformance with regulations States Department of the Interior, er points mentioned in lines 3, 4 stored, established or re-established tration for Land Surveyors or, by a
хххижжинимикиминимик В: Continued	MAKKAKKKKKKKKKKKKK	ККИККЖЖХХЖИФИК КХ	
		Frl. NW 1/4 of Sec.5 or stance to G.L.O. Survey	n line between the Ctr. /.
Fd. Ctr. of Sec.5 at The N 1/4 cor. of Sec.5 The S 1/4 Cor. of Sec.5 D-2 Fd 2" pipe for Ctr.	nd fd. old 3/4" pipe -5 is in line with a ec.32, T26N-R13W, is of Sec.5 as used by calls for 2" pipe a	25N-R13W; said N-S 1/4 e to control north end approx. ctr. of gravel s N89°28'W, 104.93'. RLS B.Batzer in 1974 sat Ctr. of Sec.5; See l	of Sd. N-S 1/4 line.
C. Description of monument for D-1	corner and accessories esta D~2	blished to perpetuate locating the	c position of the corner:
D-1 Set DNR Mon. & Ced.Pos 5" Ash N40°W 26 14" Maple N51°E 52 Fd 3/4" pipe N01°O1E 4	t Fd 2" pipe .94 *10" Scotch .10 *10" Maple	(buried 0.5) Sine S51°E 37.65 S62°W 53.12 Section 32.22 Section 53.12 Se	Set 5/8"x36"Re-Rod w/RLS Cap 18" Maple S63°E 24.49 11" Maple N38°E 40.22
	Set loc tag	g on fn.Post WZI's	B" Maple S40°W 58.13 Set Ced.Post w/loc Tag E.33' Ctr. N-S Gravel Rd. W.2'±
*Old Wits.	Set loc tag Ctr. N-S Gi	g on Fn.Post w 21° S r. Rd. E. 3' (Ctr. N-S Gravel Rd. W.2'±
*Old Wits.	Set loc tag Ctr. N-S Gi	g on Fn.Post w 21° S r. Rd. E. 3' (Ctr. N-S Gravel Rd. W.2'±
*01d Wits. SIGNED BY Call 7. K. SURVEYOR'S MICHIGAN REC	Set loc tag Ctr. N-S Gi	g on Fn.Post w 21 str. Rd. E. 3' (CARL F. ROSER LANDSEAL SURVEYOR CARL LANDSEAL SURVEYOR CARL SURVEYOR CARL SURVEYOR CARL CA
*01d Wits. SIGNED BY Call 7. K. SURVEYOR'S MICHIGAN REC	Set loc tag Ctr. N-S Gi	g on Fn.Post w 21 str. Rd. E. 3' (CARL F. ROSER LANDSEAL SURVEYOR CARL LANDSEAL SURVEYOR CARL SURVEYOR CARL SURVEYOR CARL CA
*01d Wits. SIGNED BY Call 7. K. SURVEYOR'S MICHIGAN REC	Set loc tag Ctr. N-S Gi	g on Fn.Post w 21 str. Rd. E. 3' (CARL F. ROSER LANDSEAL SURVEYOR CARL SURVEYOR CAR
*01d Wits. SIGNED BY Call 7. K. SURVEYOR'S MICHIGAN REC	Set loc tag Ctr. N-S Gi	g on Fn.Post w 21 str. Rd. E. 3' (CARL F. ROSER LANDSEAL SURVEYOR CARL SURVEYOR CAR