LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 25 N. S., R. 13 E. W.	I-1; F-1; G-1; E-1
2. PROPERTY CONTROLLING IN SECTION ____	T. ____ N. S., R. ____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION ____	T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 19, 19 80, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B. Continued;

G-1 Re-established corner common to Sec's 3&4, T25N-R13W, on S.line of T26N-R13W,and at pro-rated closing distance; said proration being to U.S. between fd. S 1/4 Cor. of S-32 & fd. S.E. Cor of S-36, T26N-R13W. The corner common to Sec's 33&34, on South line of T26N-R13W is N89°28'W 131.40 (132' - U.S.).

E-1 Re-established corner common to Sec's 4&5 T25N-R13W, on S. line of T26N-R13W and at pro-rated closing distance; said proration being to U.S. between fd.S 1/4 cor. of S-32 & fd. SE Cor. of S-36, T26N-R13W. The corner common to Sec's 32&33 on South line of T26N-R13W is N89°28'W, 98.55' (99' U.S.).

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-1 Re-established Cor. Comm to Sec's 2&3, T25N-R13W, on S.line of T26N-R13W & at pro-rated closing distance; said proration being to U.S. between fd. S 1/4 Cor. of S-32 & fd. S.E. Cor. of S-36,T26N-R13W. The corner common to 34&35 on S. line of T26N-R13W is N89°28'W 107.75' (108.2' - U.S.)

F-1 Re-established N 1/4 Cor. of Sec.4, T25N-R13W, on S. line of T26N-R13W, mid-way between the NE&NW Cor's of Sec.4. The S.1/4 Cor. of Sec. of S-33 T26N-R13W is N89°28'W 114.98'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-1

Set DNR Mon & Ced. Post
17" Maple N65°E 81.7'
20" Cherry S25°E 109.4
10" Cherry S12°W 123.8

F-1

Set DNR Mon &Ced.Post
11" Maple S33°W 29.4
12" Maple S65°E 65.8

G-1

Set DNR Mon & Ced.Post
5" Maple S34°W 64.0'
7" Maple S60°E 78.4'

E-1

Set DNR Mon & Ced.Post
6" Maple S01°E 37.6
5" (Twin) Maple S75°W 24.1

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
SEAL
REGISTERED LAND SURVEYOR

SIGNED BY Carl F. Roser 3-31-81 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

Colfax Township
BENZIE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET