LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 25 N., R. 14 W.	B-4; C-4
2. PROPERTY CONTROLLING IN SECTION 7	T. 25 N., R. 14 W.	8
3. MISCELLANEOUS PROPERTY IN SECTION 7	T. 25 N., R. 14 W.	*716.88'-W of #8

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Jan. 11, 19 79, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Jan.11, 19 79, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. continued *

Drove 5/8"X42" re-rod w/RLS Cap
& set Ced. Post w/Loc. Tag.

5" R.Pine	S43°E	39.72
5" R.Pine	S39°W	24.95
13" Apple	N37°E	73.40
Ctr. E-W Trail Due S		4'±

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-4 Set Ctr. Sec. 7 at Inter. of 1/4 lines.

C-4 Re-estab. 1/4 Cor. equidistant & on line between Sec. Cor's. to N&S. This fits fd 1/8 Cor. 1/4 mile So. & fits 1/8 Cor. position 1/4 mile No. per Rec. Plat Dist. (W line N 1/2-NW 1/4 S-8, Orchardville No. 3).

8 Established 1/8 Cor. per standard B.L.M. instructions.

* Drove 5/8"X42" rerod at NW Cor. of NE 1/4-NW 1/4-SW 1/4 of Sec.7; per std.B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-4
Drove 5/8"X36" re-rod w/Plastic Cap,
Set Ced. post w/Loc. Tag

3" cherry	N61°W	27.0
28" Pine Stp.	N19°E	60.1
4" Cherry	S75°E	23.6
2" Maple	Due S	14.5

C-4
Set DNR Mon. & Ced.Post

6" Cherry	S45°W	20.7
12" Maple	S16°E	15.4
4" Ironwood in Clump	N62°E	27.4

8
Drove 1"X30" pipe (w/RLS ca
inside 1 1/4"X24" pipe (in
open marsh)& set Ced. Post
w/ Loc. Tag.

27" Maple	S82°W	117.4
20" Tw.Maple	S58°W	50.8
30" Hemlock	S35°W	143.9
Fd. 1" pipe	N11°30'W	4.2

SIGNED BY Carl F. Roser 2-12-79 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN — SEAL — CARL F. ROSER LAND SURVEYOR No. 12028 — REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

WELDON TOWNSHIP
BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET