LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 25 N., R. 14 W.	C-3
2. PROPERTY CONTROLLING IN SECTION 7	,T. 25 N., R. 14 W.	2; 7; 14
3. MISCELLANEOUS PROPERTY IN SECTION 7	,T. 25 N., R. 14 W.	*667.71'-S. of #14

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Jan. 11, 19 79, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Jan. 11, 19 79, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. continued

14			*		
Fd. 3/4"X36" Iron rod; added plastic cap & set Ced.Post w/Loc. Tag.			Fd. 3/4"X24" Pipe & Set Ced.Post w/Loc. Tag.		
13" Cherry in clp.	S03°W	59.3	4" W.Pine	N85°W	41.7
4" W.Pine	S30°E	21.4	4" W.Pine	S50°W	58.8
8" Cherry	N72°E	42.5	3" W.Pine	N56°E	44.2

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-3 Fd. 2" angle Iron - fits old recorded plats.
2 Established 1/8 Cor. per standard B.L.M. instructions.
7 Established 1/8 Cor. per standard B.L.M. instructions.
14 Fd. Iron for 1/8 Cor. midway & on line between fd. SE Cor. Sec. 7 & Established E 1/4 Cor. Sec. 7 .
* Fd. & accepted 3/4"X24" pipe for NE corner of SE 1/4-SE 1/4-SE 1/4 of Sec. 7. Added 5/8"X36" re-rod to bottom portion of 3/4" pipe for stability.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-3			2			7		
Fd. 2" Angle Iron Add DNR Mon.& Ced.Post			Drove 5/8"X36" re-rod & Set Ced.Post w/Loc. Tag			Drove 5/8"X36" re-rod w/plastic cap & set Ced.Post w/Loc. tag.		
9" Tw.Maple	S48°W	17.8	10" Maple	S78°W	28.5	9" Maple	N26°E	10.4
7" Trp.Cherry	N21°E	20.2	3" Ironwood	S14°E	14.8	14" Tw.Maple	S28°E	24.7
4" Maple	S88°E	33.0	7" Tw.Maple	N50°W	47.7	6" Tw.Maple	S53°W	27.3

SIGNED BY Carl F. Roser 2-12-79 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

WELDON TOWNSHIP
BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET