LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

F	OR CORNERS OF -:	LOCATED				
1.	PUBLIC LAND SURVEY	т. 25	N. R. 15 W.	L-2; L-3		
2.	PROPERTY CONTROLL- ING IN SECTION-	,T	N. S., R W.			
	MISCELLANEOUS PROPERTY IN SECTION				• • • • • • • • • • • • • • • • • • •	
4.	LOT NO, REC	ORDED PLAT				
5.	PRIVATE CLAIMS				REGISTER OF DEED	_
re- an Bu an as De	Carl F. Roser e corner points mentioned in 1 established, monumented, re- d rules therefore as required a areau of Land Management or d 5 above were, in a field survexpressed below and in conforceree of a Court of law: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	ines 1 and 2 at monumented, in the current in by a decree of ey on the mance with	bove were, in a recovered or resmanual of surve a court of law.	stored as expressed below y instructions of the Uni Furthermore, that the of 19, found, recovered lichigan State Board of F	y and in conformance we ted States Department of corner points mentioned I, restored, established or	, established the regulation of the Interion in lines 3, thre-established
1	between Sec. Cor†s. 1	/2 mile to	E & W.			
В. 2	Description of corner evidence Established Ctr. Sec as noted in Co. Surv	. 1 at integrals Rec	ersection o ord II, Pgs	f 1/4 lines. No ex. 152 & 153.	vidence of Wolcott	
2 3 C.	Established Ctr. Sec as noted in Co. Surv Re-estab. 1/4 Cor. a said Comp. point bei like N'ly R.O.W. fen fence to N & S and v line with approx. Ct is 0.7'-South and 9. Description of monument for L-2 Drove 5/8"X36" re-roset Ced. Post w/Loc. 14" Maple N53° 9" R.Pine N37° 8" R.Pine N79° Ctr. of N-S B.Top rd	t Dbl. Dising 16.50 for ce (1-rod lery irregular, of co.rod lery irregular, we see the second lery irregular, lery	ersection o ord II, Pgs t & on line eet south o N. of Comp. lar wire in d. looking Comp. posi cessories establis	f 1/4 lines. No end. 152 & 153. across SW Cor. Set fd. iron, said iron trees to east. (West. 1/4 Cor reset to no f 1/4 cor. re-	vidence of Wolcott -1 and comp. 1/16 Ed. Ir. being at war being in line with the comp. 1/16 Cor. is established by this per single proporting the position of the comp. Ced. Post. 336°W 20.15	Corner, that look th old in s method
2 5 C.	Established Ctr. Sec as noted in Co. Surv Re-estab. 1/4 Cor. a said Comp. point bei like N'ly R.O.W. fen fence to N & S and v line with approx. Ct is 0.7'-South and 9. Description of monument for L-2 Drove 5/8"X36" re-ro. Set Ced. Post w/Loc. 14" Maple N53° 9" R.Pine N37° 8" R.Pine N79° Ctr. of N-S B.Top rd Due 1 Guard rail at So. end	t Dbl. Dising 16.50 for the center of the control o	ersection o ord II, Pgs t & on line eet south o N. of Comp. lar wire in d. looking Comp. posicessories establistic cap	f 1/4 lines. No en. 152 & 153. across SW Cor. Set fd. iron, said iron trees to east. (West. 1/4 Cor restion of 1/4 cor. perhed to perpetuate location. L-3 Set DNR Mon. & 12" Maple Set	vidence of Wolcott -1 and comp. 1/16 fd. Ir. being at war being in line with the comp. 1/16 Cor. is established by this per single proporting the position of the comp. Ced. Post. Ced. Post. 36°W 20.15 126°E 11.63 550°E 8.45	Corner, that look th old in s method
C	Re-estab. 1/4 Cor. a said Comp. point bei like N'ly R.O.W. fen fence to N & S and v line with approx. Ct is 0.7'-South and 9. Description of monument for L-2 Drove 5/8"X36" re-roset Ced. Post w/Loc. 14" Maple N53° 9" R.Pine N37° 8" R.Pine N79° Ctr. of N-S B.Top rd Due 1 Guard rail at So. encode Due 1	t Dbl. Dising 16.50 for ce (1-rod lery irregular, of co.rod of corner and accord dw/Plastic Tag. W 56.60 E 37.00 E 19.77 to north w 17'+ d of rd. to 30'+	ersection of ord II, Pgs t & on line eet south of the comp. It is a looking to comp. The comp. The comp. It is a looking to the com	f 1/4 lines. No en. 152 & 153. across SW Cor. Set fd. iron, said iron trees to east. (West. 1/4 Cor restion of 1/4 cor. pushed to perpetuate location. L-3 Set DNR Mon. 8 12" Maple Set Maple Set Maple No. 10" Maple Set Maple	l and comp. 1/16 It. being at war being in line wis comp. 1/16 Cor. is established by this per single proporting the position of the comp. 1/16 Ced. Post. 336°W 20.15 26°E 11.63 350°E 8.45	Corner, that look the old in s method ion (coner:
SIC SUI	Re-estab. 1/4 Cor. a said Comp. point bei like N'ly R.O.W. fen fence to N & S and v line with approx. Ct is 0.7'-South and 9. Description of monument for L-2 Drove 5/8"X36" re-roset Ced. Post w/Loc. 14" Maple N53° 9" R.Pine N37° 8" R.Pine N79° Ctr. of N-S B.Top rd Due 1 Guard rail at So. encode Due 1 CNED BY CREATER STORMS MICHICAN RECOMESTATION CONTRACTOR CON	t Dbl. Dising 16.50 for the ce (1-rod learn irregular, of co.rod). West of corner and accord w/Plastic Tag. W 56.60 E 37.00 E 19.77. to north w 17'+ d of rd. to 30'+	ersection of ord II, Pgs t & on line eet south of the comp. It is a looking to comp. It is comp. It is comp. It is a looking to the	f 1/4 lines. No en. 152 & 153. across SW Cor. Set fd. iron, said iron trees to east. (West. 1/4 Cor restion of 1/4 cor. pushed to perpetuate location. L-3 Set DNR Mon. 8 12" Maple Set Maple Set Maple No. 10" Maple Set Maple	l and comp. 1/16 It. being at war being in line with the comp. 1/16 Cor. is established by this per single proporting the position of the comp. 1/26°E 11.63 SO°E 8.45 CALLANDER OF LANDER OF LAN	Corner, that look the old in set method ion (coner:
SIC SUI	Re-estab. 1/4 Cor. a said Comp. point bei like N'ly R.O.W. fen fence to N & S and v line with approx. Ct is 0.7'-South and 9. Description of monument for L-2 Drove 5/8"X36" re-roset Ced. Post w/Loc. 14" Maple N53° 9" R.Pine N37° 8" R.Pine N79° Ctr. of N-S B.Top rd Due 1 Guard rail at So. enc Due 1 CNED BY CTRATE AND UNITED ST	t Dbl. Dising 16.50 for the center of the control o	ersection of ord II, Pgs t & on line eet south of the comp. It is a looking to comp. The comp. It is a looking to the comp. It is a	f 1/4 lines. No en. 152 & 153. across SW Cor. Set fd. iron, said iron trees to east. (West. 1/4 Cor restion of 1/4 cor. pushed to perpetuate locating. L-3 Set DNR Mon. 8 12" Maple Set Maple Set Maple Nor Maple Set	vidence of Wolcott -1 and comp. 1/16 fd. Ir. being at we have being in line with the comp. 1/16 Cor. is established by this per single proporting the position of the comp. 1/16 Ced. Post. 1.63 Ced. Post. 20.15 CALLAND F. RO	Corner, that look the old in set method ion (coner:
SIC SUI FO SIC	Re-estab. 1/4 Cor. a said Comp. point bei like N'ly R.O.W. fen fence to N & S and v line with approx. Ct is 0.7'-South and 9. Description of monument for L-2 Drove 5/8"X36" re-roset Ced. Post w/Loc. 14" Maple N53° 9" R.Pine N37° 8" R.Pine N79° Ctr. of N-S B.Top rd Due 1 Guard rail at So. encode Due 1 CNED BY CREATER STORMS MICHICAN RECOMESTATION CONTRACTOR CON	t Dbl. Dising 16.50 for the property of the pr	ersection of ord II, Pgs t & on line eet south of the ee	f 1/4 lines. No ex. 152 & 153. across SW Cor. Set fd. iron, said iron trees to east. (West. 1/4 Cor restion of 1/4 cor. period to perpetuate location. L-3 Set DNR Mon. 8 12" Maple Set	l and comp. 1/16 fd. Ir. being at we being in line with comp. 1/16 Cor. is established by this per single proporting the position of the comp. Ced. Post. Ced. Post. Cal. Soo'E 11.63 Soo'E 8.45	Corner, that look the old in set method ion (coner: