LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
L PUBLIC LAND SURVEY	T. 26 R. 13	I-10; I-11; H-11	
2. PROPERTY CONTROLL- ING IN SECTION- · ·	,T N. R W.		
3. MISCELLANEOUS PROPERTY IN SECTION	,T		
4. LOT NO	ORDED PLAT		
5. PRIVATE CLAIMS	· · · · · · · · · · · · · · · · ·		REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in lare-established, monumented, reand rules therefore as required. Bureau of Land Management or and 5 above were, in a field surv	ines 1 and 2 above were, in a fi monumented, recovered or rest in the current manual of survey by a decree of a court of law, cy on	tity that under requirements of eld survey on November ored as expressed below and instructions of the United Sta Furthermore, that the corner	P.A. 74, Michigan P.A. of 1970, 177,, 1980, established, in conformance with regulations des Department of the Interior, points mentioned in lines 3, 4 red, established or re-established tion for Land Surveyors or, by a
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	, Жака кака кака жаза кака ка кака ка жа	kannannannannan:	
E'ly a short distand for 1/4 Cor. to Sec'	se to 5wp. & W'ly(most s 26 &27.	ly gone) 1/2 mile. Ac	ccepted 36" W. Pine Stub
swamp edge to West. I-10 Fd.36"x6 1/2' W.Pine (May 1839) call for There is a possible Mich. R.R. tie of (7 an old E-W(Skewed)fe C. Description of monument for H-11 Set.DNR Mon &Ced.Post 7" Maple N47°E 24.2	corner of S-27 equidis r. of S-27 at pro-rate c. Corner and at U.S. stub with real old N- "Pine 36'in-dia, Qt.Se Hem. hummock site N60° 84'-Rec.) 785.9'± Comp nce, mostly down, 50'± corner and accessories establish I-11 Set DNR Mon.im 1 1/2" 1' above Grd & added	stant & on line between distance to U.S. 1/dist. West (892') to S.B-W fence remain's ec.Cor. (BT)Hemlock 150 E. 14'. Corner also S. to Ctr. of Exist South of 36" W.Pine ed to perpetuate locating the power of the p	n Sec. Cor's to E&W. 2 mile north to 1/4 cor. stream which fits tie to on it. U.S. line notes N60E 21 links (13.9')". fits 1891 Chicago & West R.R.tracks. There is stub. The fence goes oxition of the corner: I-10 R Mon.on 1"x30" pipe
8" Maple N63°W 34.7 9"Maple \$14°W 40.4 Rand.East North 3.0' SIGNED BY 7. Po SURVEYOR'S MICHIGAN REG FOR STATE AND UNITED ST. SIGNED BY	ISTRATION NO. 12028 ATES AGENCIES:	DATEDATE	CARL ROSER LAND SERVICE OF LAN
APPROVED AND SIGNED BY_	MICHIGAN REGISTERED LAND :	DATE	(SEAL)
SURVEYOR'S MICHIGAN REG	STRATION NO		nland Township ENZIE COUNTY