## LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

L. Carl F. Roser	FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
A MISSICIANNOS PROPERTY IS SECTION.  RECORDED PLAT.  S. PRIVATE CLAIMS  I. Carl F. Roser  It comes points minitioned in lines 1 and 2 above were, in a field survey on.  November 18, 10, 20, 30, established re-established, manumented, re-monamented, recovered or unforced and expensed below and in conformance with exposition and used functioned to the Curter annual of survey instructions of the United States Department of the International August International Control law.  Manufacture were, that field survey on.  Movember 18, 10, 20, 30, established re-established, manumented, re-monamented, recovered or unforced and incomposition of the United States Department of the International Control law.  Manufacture were, that field survey on.  Movember 19, 10, 40, 60, established concerpoints mentioned as lines as a supersed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by Decrete of Scott of law.  MAXEMARKAMAKAMAKAMAKAMAKAMAKAMAKAMAKAMAKAMAK	1. PUBLIC LAND SURVEY	T. 26 N. R. 13 W.	B-12; B-13; A-13	
S. PRIVATE CLAMS  1. Carl F. Roser  the corner points mentioact in lines L and 2 above were in a field server on. Hovember 18, 74, Michigan P.A. of the corner points mentioact in lines L and 2 above were in a field server on. Hovember 18, 19, 00, cetablish exestablished, monitorial control of server of a capture of the trining of the corner points mentioned in the corner in manual of survey instructions of the United States Department of the bases in a field server on. In the server of a court of law. Furthermore, Perthermore, that the conner points mentional in lines 3, and 3 above were in a field server on. In 19, found, recovered, established or restablished see expressed below and in conformance with the roles of the Michigan State Board of Registration for Land Surveyors on, by Dever of a Court of law.  XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	2. PROPERTY CONTROLA ING IN SECTION	31 ,T 26 N. 13 W.	5	
Example 1. Carl F, Roser do hereby certify that under representation of P.A. of A Michigan P.A. of 19 the corner points mentioned in lines 1 and 2 above were in a field survey on November 18. 19. 90 establish examples of P.A. of 19 the corner points mentioned in lines 1 and 2 above were in a field survey on November 18. 19. 90 establish examples therefore as required in the current annual of survey instructions of the United States Department of the Intention Beacon of Lord Management or by a decree of a court of law. Particulare, that the corner points machinal in lines 3, and 5 above were in a field survey on 19. (ound, recovered, restored, established or re-exablished as expressed below and in conformance with the rules of the Michigans State Board of Registration for Land Surveyors or, by Decree of a Court of law.  XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	3. MISCELLANEOUS PROPERTY IN SECTION	N. E. W. S., R W.		
I. Carl F. Roser  do hereby certify that under requirements of P.A. 74 Michigan P.A. of Unitable the corner points mentioned in lines 1 and 2 above were, in a field survey on November 18. 19.80 exhibits re-exhibited, monimicated, re-ordered or restored as expressed below and in conformance with regulational rules therefore as required in the current manual of survey instructions of the United States Department of the Internal Business of Land Minagement of by a derive of a count of the Pinted States Department of the Internal Business of Land Minagement of the Internal State Board of Registration for Land Surveyors on a field survey on and 5 above were, in a field survey on the Pinted State Board of Registration for Land Surveyors on the December of a Count of law.  ***XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	i. LOT NO	RECORDED PLAT		
I. Carl F. Roser  the corner points mentioned in lines 1 and 2 above were, in a field survey on ROVERDER 13. 19 80, established re-established, monomimented, re-monamented, recovered or restored as expressed below and in conformance with regions and relate therefore as respired as the recovery of the theorem of the latern Bureau of Land Management or by a devere of a centr of law. Furthermore, that the conner points mentioned in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended states Department of the latern Bureau of Land Management or by a devere of a centr of law. Furthermore, that the conner points mentioned in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, extended in lines 3, and 5 above were, in a field survey on 19. [mund, recovered, recovered or 19. [mund, recovered or	5, PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
The rother panels mentioned in lines I and 2 above were, in a feld survey on restablished, monumented, resonanced, resonanced or restored as expressed below and in conformance with regulate and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior Burcas of Land Management or by a deveree of a count of law. Furthermore, that the canner points mentioned in lines 3, and 5 above were, in a field survey on 192	0 1 5 0			FILING NUMBER
A-13 Fd. R.R. Iron Fd. Benzie Co. Mon. 10" Maple N25"E 64.5 10" Maple N28"W 71.1 10" Maple S48"E 77.63 Set Ced. Post W/loc tag N 33 12" Maple S48"E 77.64  (rr. E-W Gravel Rd N 5' Set Ced. Post N45"E 47.5  B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  8-12 Established Center of Sec. 31 at intersection of one-quarter lines. 5 Established NE Cor. of SE 1/4 of fr1. NW 1/4 of S-31, equidistant & on line between N 1/4 Cor. & center of S-31. Fd 1"22" iron at old fn. corner, fn remains west & irregular fn north; said iron being S00°45'W 22.7' Fram establishing corner:  8-13 Found R.R. rail buried on end, per old county surveyor's record, Sec.31, J.A. Pettet Co. Surveyor; large brown Co. Surveyor's liber "0", Pg's 16 & 17. The N 1/4 Cor. of Sec.6, T25N-R13W, found 3" pipe, is 35.93' - East and 0.50'-south of straight line (TWP.Line) between the S 1/4 Cor. & SE Cor. of Sec.31.  8-13 Fd. Std. Benzie Co. mon. in.ctr. of N-S bl. top Co. Rd. Ctr. of gravel rd to East is 2' DAWEDING LATING MAN	the corner points mentioned re-established, monumented and rules therefore as requibureau of Land Manageme and 5 above were, in a field as expressed below and in	I in lines I and 2 above were, in a l, re-monumented, recovered or re- ired in the current manual of survent or by a decree of a court of law l survey on	estored as expressed below and ey instructions of the United S. Furthermore, that the corner 19, found, recovered, rest	in conformance with regulation tates Department of the Interior points mentioned in lines 3, ored, established or re-established
Fd. R.R. Iron  10" Maple N25°E 64.5 *28" Maple N71°E 90.35 10" Maple N28°W 71.1 , *11" Maple S34°E 77.63 Set Ced. Post w/loc tag N 33 *21" Maple S34°E 73.40  Crr. E-W Gravel Rd N 5' Set Ced. Post N45°E 47.5  B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  B-12 Established center of Sec. 31 at intersection of one-quarter lines.  5 Established NE Cor. of SE 1/4 of frl. NW 1/4 of S-31, equidistant & on line between N 1/4 Cor. & center of S-31. Fd 1"x24" iron at old fn. corner, fn remains west & irregular fn north; said iron being S00°45'W 22.7' From estable.  5 Found R.R. rail buried on end, per old county surveyor's record, Sec. 31, J.A. Pettet Co. Surveyor; large brown Co. Surveyor's liber "0", Pg's 16 & 17. The N 1/4 Cor. of Sec. 6, T25N-R13W, found 3" pipe, is 35.93' - East and 0.50'-south of straight line (Twp.Line) between the S 1/4 Cor. & SE Cor. of Sec. 31.  5 Fd. Std. Benzie Co. mon, in ctr. of N-S bl. top Co. Rd. Ctr. of gravel rd to East is 2'. DOURN BROWN MONOTOR WARD CONTROL MARK Collaboration of the corner: B-12 Set 5/8"x36" Re-Rod w/RLS cap Set Ced. Post w.loc Tag. Set Ced. post W.loc Tag. 12" Maple S77°W 9.4 5" Maple N34°E 15.5 12" Maple S77°W 9.4 5" Maple N34°E 15.5 12" Maple S20°E 9.8 6" Maple S18°E 16.5' 6" Maple N12°E 16.6 5" Maple S18°E 16.5' 6" Maple N12°E 16.6 5" Maple S71°W 10.0'  * Old Wit's  SIGNED BY CALl From Earth Country DATE.  APPROVED AND SIGNED BY DATE.  **CHICHIGAN REGISTRATION NO. 12028  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY CALL FROM COUNTY DATE.  **CHICHIGAN REGISTRATION NO. 12028  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY DATE.  **CHICHIGAN REGISTRATION NO. 12028  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY DATE.  **Inland Township BENNIE COUNTY DATE.  **Inland Township BENNIE COUNTY DATE.		_	:ХИЖДИККИ ИКИ И И И И И И И И И И И И И И И	
10" Maple N28" 71.1 , *   Maple S49"E 77.63 Set Ced. Post w/loc tag N 33 *21" Maple S34"E 73.40  (rr. E-W Gravel Rd N 5" Set Ced. Post N45"E 47.5  B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  B-12 Established center of Sec. 31 at intersection of one-quarter lines.  5 Established NE Cor. of SE 1/4 of frl. NW 1/4 of S-31, equidistant & on line between N 1/4 Cor. & center of S-31. Fd 1"x24" iron at old fn. corner, fn remains west & irregular fn north; said iron being S00"45"W 22.7" from estable. Cor.  3-13 Found R.R. rail buried on end, per old county surveyor's record, Sec.31, J.A. Pettet Co. Surveyor; large brown Co. Surveyor's liber "0", Pg's 16 & 17. The N 1/4 Cor. of Sec.6, T25N-R13M, found 3" pipe, is 35.93' - East and 0.50'-south of straight line (Twp.Line) between the S 1/4 Cor. & SE Cor. of Sec.31.  4-13 Fd. Std. Benzie Co.mon. in ctr. of N-S bl., top Co., Rd. Ctr. of gravel rd to East is 2'  5-60W#floof-brownfintMed-bracks rade at 0.888-teclablished M9Etakunte locating the position of the corner:  Set 5/8"x36" Re-Rod w/RLS cap	Fd. R.R. Iron	Fd. B	Benzie Co. Mon.	
Description of corner evidence found and/or method applied in restoring or re-establishing corner:  8-12 Established center of Sec. 31 at intersection of one-quarter lines.  5 Established NE Cor. of SE 1/4 of fr1. NN 1/4 of S-31, equidistant & on line between N 1/4 Cor. & center of S-31. Fd 1"x24" iron at old fn. corner, fn remains west & irregular fn morth; said iron being S00°45'W 22.7' From estable. Cor.  3-13 Found R.R. rail buried on end, per old county surveyor's record, Sec.31, J.A. Pettet Co. Surveyor; large brown Co. Surveyor; liber "0", Pg's 16 & 17. The N 1/4 Cor. of Sec.6, T25N-R13W, found 3" pipe, is 35.93' - East and 0.50'-south of straight line (Twp.Line) between the S 1/4 Cor. & SE Cor. of Sec.31.  4-13 Fd. Std, Benzje Co. mon. in ctr. of N-S bl. top Co. Rd. Ctr. of gravel rd to East is 2'. Description of the corner:  8-12 Set 5/8" x36" Re-Rod w/RLS cap Set Ced. post w.loc Tag. Set Ced. post w.loc Tag. Set Ced. post w.loc Tag. Set Ced. post w/loc tag. 12" Maple S77"W 9.4 5" Maple N34°E 15.5  12" Maple S20°E 9.8 6" Maple S18°E 16.5'  6" Maple N12°E 16.6 5" Maple S18°E 16.5'  8 Old Wit's SIGNED BY APPROVED AND SIGNED BY DATE.  APPROVED AND SIGNED BY DATE.  CHIEF OF SURVEY PARTY DATE.  APPROVED AND SIGNED BY DATE.  CHIEF OF SURVEY PARTY DATE.  APPROVED AND SIGNED BY DATE.  CHIEF OF SURVEY PARTY DATE.  APPROVED AND SIGNED BY DATE.  Inland Township BENNIE COUNTY	•	25°E 64.5 *28"  28°W 71.1 *11"	Maple N71°E 90 Maple S48°E 77	
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  8-12 Established Center of Sec. 31 at intersection of one-quarter lines.  5 Established NE Cor. of SE 1/4 of frl. NW 1/4 of S-31, equidistant & on line between N 1/4 Cor. & center of S-31. Fd 1"x24" iron at old fn. corner, fn remains west & irregular fn north; said iron being S00°45'W 22.7' From estable.  3-13 Found R.R. rail buried on end, per old county surveyor's record, Sec.31, J.A. Pettet Co. Surveyor; large brown Co. Surveyor's liber "0", Pg's 16 & 17. The N 1/4 Cor. of Sec.6, 125N-R13W, found 3" pipe, is 35.93' - East and 0.50'-south of straight line (Twp.Line) between the S 1/4 Cor. & SE Cor. of Sec.31.  4-13 Fd. Std, Benzie Co.mon. in ctr. of N-S bl.top Co.Rd. Ctr. of gravel rd to East is 2' Countification of the connect B-12  Set 5/8"x36" Re-Rod w/RLS cap	Set Ced. Post w/	loc tag N 33 *21"		.40
Established center of Sec. 31 at intersection of one-quarter lines.  5				
SIGNED BY Carl 7. Posit 2/20/81  SURVEYOR'S MICHIGAN REGISTRATION NO. 12028  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY DATE  CHIEF OF SURVEY PARTY  APPROVED AND SIGNED BY DATE  MICHIGAN REGISTERED LAND SURVEYOR  (SEAL)  Inland Township BENXIE COUNTY	B-12 Established cent 5 Established NE C N 1/4 Cor.& cent irregular fn nor B-13 Found R.R. rail Co. Surveyor; la Sec.6, T25N-R13W (Twp.Line) betwe 4-13 Fd. Std. Benzie B-14 Fd. Std. Benzie Set 5/8"x36" Re-	er of Sec. 31 at interse or. of SE 1/4 of frl. NW er of S-31. Fd 1"x24" ith; said iron being SOO° buried on end, per old crge brown Co. Surveyor's, found 3" pipe, is 35.9 en the S 1/4 Cor. & SE Co.mon. in ctr. of N-S bwqotrackr ratiatesswastesiable Rod w/RIS can	ction of one-quarter 1 1/4 of S-31, equidist ron at old fn. corner, 45'W 22.7' From estab ounty surveyor's recordiber "0", Pg's 16 & 3' - East and 0.50'-scor. of Sec.31.  1 top Co.Rd. Ctr. of contact to 90 ctr. at least 10 ctr. of contact to 90 ctr. at least 10	ines. cant & on line between fn remains west & cor. rd, Sec.31, J.A. Pettet 17. The N 1/4 Cor. of buth of straight line gravel rd to East is 2's position of the corner: 1/RLS Cap & 5.5 6.5' 0.0'
SURVEYOR'S MICHIGAN REGISTRATION NO. 12028  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY			agraph.	E O WICKLING
SURVEYOR'S MICHIGAN REGISTRATION NO. 12028  FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY	SIGNED BY Carl 7	1. Roser 2/20/81	DATE	F. ROSER LAND
FOR STATE AND UNITED STATES AGENCIES:  SIGNED BY				12028
APPROVED AND SIGNED BY DATE		• •	- "	CAED LAND SULLING
APPROVED AND SIGNED BY DATE	SIGNED BY		DATE	
(BEAL) Inland Township BENXIE COUNTY	APPROVED AND SIGNED	CHIEF OF SURVEY PARTY	DATE	
BENXIE COUNTY '		MICHIGAN REGISTERED LAN		(SEAL)
STOREST STATE OF THE STATE OF T	CHDARVADE AGERTO	DECUCED VEION VO	BE	