LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. ●, R. 13 ● W.	A-12; B-11; C-12
2. PROPERTY CONTROLLING IN SECTION 31	,T 26 N. ●, R. 13 ● W.	10
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 18, 19 80, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued.

B-11

Fd. Benzie Co. Mon (Flush w/grd)
Added Ced. Post w/loc tag

11"	Cherry	N65°E	41.52
20"	Cherry(Twin)	S55°E	31.25
8"	R. Pine	S30°E	25.38
Ctr.	E-W dirt rd.	N	34'±

C-12

Set D.N.R. Mon & Ced Post

6"	Ironwood	S07°E	20.9
11"	Maple	N50°E	11.5
10"	Maple	N30°W	29.1

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-12 Found 3/4" pipe in mon. box for W 1/4 Cor. of S-31.

10 Established S 1/8 cor. on W. line S-31, equidistant & on line between the W 1/4 cor. & the SW corner of Sec. 31. Corner is in line with trail road to east. Set Cedar post w/loc tag, 33' W, but land owner removed same.

B-11 Fd. Std. Benzie County monument. N-S fence to North on E. side of Spruce Plantation is 27'± east.

C-12 Re-established E 1/4 cor., Sec.31, equidistant & on line between NE & SE cors. of S-31.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-12

Fd 3/4" pipe in Mont. Box

* 8"	R. Pine	N71°E	47.69
*10"	R. Pine	S44°E	64.38
Set Ced. Post w/loc tag		E	33'
Ctr. N-S B.T. Rd.		E	1'

10

Set 1" x 18" rod

11"	Maple	N49°W	37.29
7"	Maple	S69°W	39.40
6"	R.Pine	S60°E	48.22
Ctr. N-S Bit. Rd.		E	3'

*Old Wit's

SIGNED BY Carl F. Roser 2/20/81 DATE

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

Inland Township
BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET