LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

CORNER CODE NUMBER

LOCATED IN -:

FOR CORNERS OF -:

1. PUBLIC LAND SURVEY T. <u>26</u> , R	13 w: G-	10; G-11; H-9		
2. PROPERTY CONTROLL- 27 ,T. 26 N. ING IN SECTION- 27 ,T. 26 N. R.	13 w 3			
3. MISCELA.ANEOUS PROPERTY IN SECTION, T S., R				
i. LOT NO , RECORDED PLAT	·		i ·	
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAN	IP AND
1, Carl F. Roser , do he the corner points mentioned in lines 1 and 2 above were-established, monumented, re-monumented, recovere and rules therefore as required in the current manual of Bureau of Land Management or by a decree of a court and 5 above were, in a field survey on as expressed below and in conformance with the rules Decree of a Court of law:	re, in a field sid or restored of survey justrof law. Furth	as expressed below actions of the Unit ermore, that the c _, found, recovered	ember 17, 1980, est and in conformance with re ed States Department of the orner points mentioned in hi , restored, established or re-es	cablished, egulations Interior, nes 3, 4 tablished
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx C. Continued:	<i></i> Қ Ж ҚҚҚҚҚҚҚҚҚ	XXXXXXXXXX XX		
G-10 Set l"x18" Rod (buried 0.5) 12" Maple (cluster) N55°W 14.2 8" R. Pine S44°W 59.9 12" Maple (cluster) N06°W 84.1 Set Ced. Post w/loc Tag W. 16.5	18" (2 4" (G-11 ONR Mon. & ced Dak (twin) Dak (Twin) Ash (twin)	S78°W 15.7	
H-9 Fd. Iron w/RLS Cap. 3 Estab. N 1/8 Cor. on W. line of Sec. & 1/4 cor. to So. Corner falls about G-10 Re-estab. W 1/4 Cor. of S-27 equidist falls in West wheel track of N-S two G-11 Re-Estab. SW Corner of S-27 at sing line across 1/4 Cor. & Sec. Cor. to s.p. 1/4 Cor. to E. which fits N-S to Sec. Sec. Sec. Sec. Sec. Cor. to Se	t mid-way stant & on o-track tra le-proport North whi	between old 50 line between ail road. ion to U.S. fo ch fits road 8	O' N-S R.O.W. fences. Sec. Cor's to N & S. Or 1-mile N&S and on s	Corner straigh
C. Description of monument for corner and accessories			- ·	
H-9 Fd Ir. w/ RLS Cat #13030 *14" Basswood S40°E 68.21 12" Maple S37°E 84.03 31" Oak N60°W 91.00 *Cor. Fn Post S. 28.84 Set Ced. Post w.loc Tag S. 27' Ctr. E-W Bit Rd. N. 6'	Set 5/8": & added 8" Map 8" Map 8" Map Ctr. N-S	(36" Re-Rod w, Ced. Post w/lo le N62°W le N70°E le S31°W Trail Rd E.	RLS Cap oc. Tag 19.3 39.8 16.7 10'	
*Old Witts Cal 7. Roser	2/20/81	DATE	F. ROSER	
SURVEYOR'S MICHIGAN REGISTRATION NO	12028		No. 12025	
FOR STATE AND UNITED STATES AGENCIES:		=	TANAPED LAND SURFIELD	
SIGNED BYCHIEF OF SURVEY PARTY		DATE		
APPROVED AND SIGNED BY MICHIGAN REGIST	TEREN LAND SHRV	DAT:	E	
MICHIGAN REGIS	FOUR SOUA	- · - "	(SEAL)	
SURVEYOR'S MICHIGAN REGISTRATION NO			Inland Township BENZIE COUNTY	
F	ORM APPROVED	BY MICHIGAN STATE	BOARD OF REGISTRATION, JAN. REVISED MAY	

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET