LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 26 N., R. 14 W.	C-5
2. PROPERTY CONTROLLING IN SECTION 8	,T. 26 N., R. 14 W.	11; 12
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on September 30, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-5 Found 3/4" "T" iron w/cap in mon. box in N-S blacktop road with road to E and W.

11 Established center of SW¼ Sec. 8 at intersection of one-eighth lines. Old corner fence post as set by the older Mr. Worden (fence N&E) without survey is 2'± NW.

12 Drove 5/8" rerod (in lawn) midway and on line between center section N and ¼ corner S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-5			11			12		
Fd. 3/4" "T" iron w/cap in monument box			Set 5/8"x36" rerod & cedar post w/loc. tag			Set 5/8"x36" rerod in lawn flush (no post)		
"T" Pole	S77°W	50.58	5" Maple	N13°E	33.0	24" Maple	S87°W	52.21
SW corner conc. block bldg.			10" Maple	N66°E	53.0	9" Twn.Maple	N66°E	55.53
	N35°E	81.9	6" Maple	N88°E	53.0	32" Maple	Due S	43.51
10" Locust	S33°E	61.28						

SIGNED BY Carl F. Roser DATE 10-31-77

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

HOMESTEAD TOWNSHIP
BENZIE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET