LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NU	MBER
1. PUBLIC LAND SURVEY.	т. <u>26</u> ., к. 13	B w. D-7. D-5	
2. PROPERTY CONTROLL-17 ING IN SECTION—17	,T. 26 N., R. 13	3 . 12, 15	
3. MISCELLANEOUS PROPERTY IN SECTION			
4. LOT NO , RECO	ORDED PLAT		wasana.
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
			FILING NUMBER
the corner points mentioned in his re-established, monumented, re-nand rules therefore as required in Bureau of Land Management or land 5 above were, in a field surve	nes 1 and 2 above were nonumented, recovered to the current manual of by a decree of a court by on	e, in a field survey onD l or restored as expressed b of survey instructions of the of law. Furthermore, that t , 19, found, recov	percented by the corner points mentioned in conformance with regulations. United States Department of the Interior, the corner points mentioned in lines 3, 4 wered, restored, established or re-established of Registration for Land Surveyors or, by a
NX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	ሟዝ <i>ኳ እነ</i> ደ <u>ዊ አነ</u> ድ ዊ ጽ ብጂርት አ	ደርፈላንአ ጽ <i>ዘበማ</i> ማ የተማለማ አ <i>ተ</i> ማ መቀው ነ	ŧ
C. (cont.)	D-5		
fd. P.K. i 4" W Pine		S30°E 64.90	
8" H. Map1	e :	S60 ⁰ W 64.85	
Rd. C.C. M Ctr line o		S 33.00 N 16.0'	
South edge	of E-W		·
Blacktop r	d (in curve)	N 6.1'	_
Sec. 17. Corner fall	S line of Sec. s in N wheel tra ail in black-top	17 midway & on line ack of E-W winding t p widening (US-31) a	e bet. S1/4 cor. & SW cor. of two-track. Is previously used in Cert.
C. Description of monument for 12			
Fd. Cade mon. & added c	ed. Fd. Cade	mon. (buried 0.5)	15 Set 5/8" x 36" rerod w/RLS cap (buried 0.5) 10" Maple N20°W 11.3 13" Maple N15°E 18.9 8" Maple S15°W 24.7 Fd. Cade mon. (top broke off) N44°W 6.5′ Set ced. post w/loc tag
post w/loc tag. 12" Maple NO5°E 31	.5 *9" Maple	e S35°E 17.8	10" Maple N20°W 11.3
13" Maple \$75°E 6	.3 *9" Maple	e \$20°W 23.0	13" Maple N15°E 18.9
N-S Random West 4	.9 Ctr. E-W	South 3't	Fd. Cade mon. (top broke off)
	Set ced.	post w/loc tag	N44°W 6.5′
	*=Cade W	Norm 10.5	North 16.5
STONED BY Cal 7 A	Paser 12	-10-82 DATE	S STOP MAY
SIGNED BY COC 777	<u> </u>	70 00 DATI	THE TOWNS OF THE PARTY OF THE P
SURVEYOR'S MICHIGAN REC	DISTRATION NO	12028	S CARL 2
SIGNED BY CAL 7, A SURVEYOR'S MICHIGAN REC FOR STATE AND UNITED ST	TATES AGENCIES:		* LAND SURVEYOR
SIGNED BY	CHIEF OF GIIDNEY BADY	DATI	E 12028
APPROVED AND SIGNED BY	MICHIGAN REGIS	TERED LAND SURVEYOR	DATE JAND SURFIELD (SEAL)
SURVEYOR'S MICHIGAN REC	CISTRATION NO.		F. ROSER LAND SURVEYOR 12028 DATE INLAND TOWNSHIP BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975
MAY PLACE SKETCH ON BACK OR ATTACHED SHEET