LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. S., R. 13 E. W.	D-6,
2. PROPERTY CONTROLLING IN SECTION 17	T. 26 N. S., R. 13 E. W.	5, 8, 9, 16
3. MISCELLANEOUS PROPERTY IN SECTION ____	T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____, RECORDED PLAT ____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 10, 19 81, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

C. Continued:

9

Drove 5/8" x 36" rerod w/RLS cap (buried)

9" Maple	N25°E	53.0
10" Maple (twin)	N55°W	31.2
6" Maple	S15°W	41.1

Set ced. post w/loc. tag.

South 16.5

Fd. T. Ir. w/cap #10681 N87°54'E 34.25

16

Fd. Cade mon. & added ced. post w/loc. tag.

*14" W. Pine	N05°E	22.0
*20" Maple	N70°W	49.4
*8" Maple	N45°E	4.0

*=Cade Wits

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

5 Established NE cor of S1/2 of NW1/4 of Sec. 17 midway & on line bet. fd. ctr. & N1/4 cor. of Sec. 17.

8 Fd. Cade monument for W1/8 cor. on E-W 1/4 line, Sec. 17.

D-6 Fd. Cade Sq. conc. mon. as established in July 1939 at intersection of 1/4 lines.

9 Estab. E1/8 cor on E-W 1/4 line of Sec. 17 midway & on line bet. fd. Cade mon's. for ctr. & E1/4 cor. of Sec. 17. Ctr. of E-W trail road is 2'± north.

16 Fd. & accepted Cade (1939) sq. conc. monument for E1/8 corner on South line of Sec. 17.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5

Set 5/8" x 36" rerod w/RLS cap & ced. post w/loc tag.

3" Maple	N10°E	11.2
6" Maple	S25°E	13.0
8" Maple	S70°W	17.6

8

Fd. Cade mon. & added ced. post w/loc tag.

*39" Maple	S80°E	95.6
*14" Poplar	N30°W	36.5
7" W. Pine	S65°W	52.2

*Cade Wit. of July 1939

D-6

Fd. Cade mon. & added ced. post w/loc. tag.

*11" Maple	S85°W	26.2
*10" Maple	S80°E	42.2
9" Maple	N70°E	28.45
*10" Basswood (cluster)	N25°W	6.08

*=Cade Wits of July 1939

SIGNED BY Carl F. Roser 02-10-82 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN — CARL F. ROSER — LAND SURVEYOR — No. 12028 — REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

INLAND TOWNSHIP
BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET