LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 27 N. S., R. 13 E. W.	A-1; A-4; B-1; C-1
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 3, 19 80, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

B-1

Fd. 4" rd. conc. mon. w/rod & RLS cap 13026; added ced. post w/loc tag.

*24" Apple	N10°W	46.13
*20" Maple	N58°W	63.63
* 5" Maple triple	S48°E	95.40

* = Old Wits

ctr. E-W winding gravel road) in curve North 100'±

C-1

Fd. Benzie Co. mon.

7" Maple	S23°W	54.49
7" Maple	S65°W	59.60
28" Elm stp.	S40°E	34.8
℄ E-W Gr. rd.	North	4'±

Fn. N is 2'± E.

Ced. post w/loc tag	S	33'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-1 Fd. rod with RLS cap for NW cor. of Sec. 6. Corner fits old witnesses.
A-4 Reestablished W 1/4 cor. of Sec. 7, equidistant & on line bet. SW & NW corners of S-7.
B-1 Fd. round conc. mon. with rod & RLS cap #13026; for N 1/4 corner of Sec. 6.
C-1 Found std. Benzie Co. mon. for NE corner of Sec. 6.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-1

Fd. rod w/RLS cap

*38" Maple	N18°E	65.31
*24" Maple	N69°E	72.45
* 7" Cedar	S34°E	30.85
Set ced. post w/loc tag	S	16.5
ctr. E-W gr. rd.	N	2'±

* = Old Wits

A-4

Set DNR mon. & ced. post

10" Maple	N40°W	27.9
12" Maple	N40°E	8.9
11" Maple	S70°E	9.8

SIGNED BY Carl F. Roser 3-16-81 DATE

STATE OF MICHIGAN — CARL F. ROSER LAND SURVEYOR No. 12028 — REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

ALMIRA TOWNSHIP
BENZIE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET