

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>BENZIE</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>27N</u> R <u>13W</u>	_____
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S <u>30</u> T _____ R _____	<u>2, 16</u>
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

RECEIVED
JUN 23 1997
P.A. 74, MICHIGAN P.A. 1970

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CARL T. KIISKILA, in a field survey on OCTOBER 21, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	10		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:
2 _____ 16 _____



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
2 _____ 16 _____
ESTABLISHED THE NE COR. OF NW1/4 OF NE1/4 OF S-30 PER STANDARD B.L.M. INSTRUCTIONS. ESTABLISHED THE SE COR OF SW1/4 OF SE1/4 OF S-30 PER STANDARD B.L.M. INSTRUCTIONS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
2 _____ 16 _____
SET 5/8" x 34" REROD W/PS CAP AND BLUE CARSONITE POST W/LOC TAG.
9° TW.S.MAPLE N53°W 14.45'
10° MAPLE (CLP 4) N20°E 2.93'
4° S.MAPLE S48°E 13.87'
10° TW.MAPLE S12°E 5.21'
SET 5/8" x 34" REROD W/PS CAP.
2" R.PINE N32°W 38.25'
5" SCOTCH PINE (CLP 4) N24°E 64.31'
5" TW.B.CHERRY S40°E 53.70'
2" TW.R.PINE S56°W 46.59'
SET CARSONITE POST W/LOC TAG NORTH 33'
CTR. OF E-W GRAVEL RD. SOUTH 6'

Signed by Carl T Kiiskila Date 4-9-97
Surveyor's Michigan License No. 33981