LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN-	!	CORNER CODE NUMBER		
	1. PUBLIC LAND SURVEY	T S.,	R E.			
	2. PROPERTY CONTROLL. 2 ING IN SECTION—	25 ,T. 27 N.	R. 15 W.	2, 6, 9		
	3. MISCELLANEOUS PROPERTY IN SECTION 2	25_ ,127 ^N .,	R. 15 W.	XX= _1448'W of M-10		
	4. LOT NO, RECORDED PLAT					
	5. PRIVATE CLAIMS				REGISTER OF DLEDS ST FILING NUMBE	
	I, <u>Carl F. Roser</u> , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on <u>January 27</u> , 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on <u>January 26</u> , 19, 81, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:					
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX						
B. C.	Continued: 9 Drove 1" x 6' pipe w			Fd. round conc.	XX	post w/loc
	post w/loc tag.		28.62	tag. 8" Cedar	N31°W	12.69
	O" Hemlack	N79°W S36°E	11.57	8" Cedar	S74°E	12.88
	7" Maple	N38°E	24.72	7" Hemlock		9.19
	Fd. "T" Ir.	S88°51'W	5.05	E. edge Platte L	ake W	20'±
	B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: Set E 1/8 cor. on N line of Sec. 25 equidistant & on line between NE corner & N 1/4 cor. of Sec. 25. The ctr. of gravel road to east is 55'± North. Set center of NE 1/4 of Sec. 25 (NE corner of Govt. Lot 3) per std. BLM instructions. See working drawing & survey of Sec. 25 by RLS, H. R. Bruning for Sleeping Bear Dunes Nat. Park (77-1975). Established E 1/8 cor. on E-W 1/4 line (SE cor. of Govt. Lot 3) of Sec. 25 on line bet. fd. E 1/4 cor. & fd. M.C. cor. on East side of Little Platte Lk. and at 1/4 distance bet. E1/4 cor. & W1/4 cor of Sec. 25 or 1313.95'W of E1/4 cor. See survey of Sec. 25 by RLS, H.R. Bruning for Sleeping Bear Dunes Nat. Park (44-1975). Ed. Corc. mol. for M.C. cor. on Established & perpendict Lk. and the position of time corner and accessories established to perpendict beauting the position of time corner. Mon. is 2 Drove 1 1/4" x 18" rod in B. top (M-22) Drove 5/8" x 36" rerod w/RLS cap & set					
	Drove 1 1/4" x 18" r	od in B. top	(M-22)	Drove 5/8" x 36"	rerod w/RLS cap	& set
	14" W. Pine	N45°W	30.60	8" Maple	N35°E	32.5
	12" W. Pine	S75°W	62.36	7" Maple 5" Hemlock	N60°W รธร _ิ ผ	35.9 43.5
	Fd. FCW 3/4" pipe Ctr. of M-22	NO1°15'E East	28.01 2'±	Drove 5/8" x 36" ced. post w/lo 8" Maple 7" Maple 5" Hemlock Ctr. N-S Power L	ine West	3'±
	SIGNED BY Carl 7 SURVEYOR'S MICHIGAN I	REGISTRATION N	120	DATE_	CARL F. ROSER LAND SURVEYOR NO. 12028 RED LAND SURVEYOR	
FOR STATE AND UNITED STATES AGENCIES: SIGNED BY					Thursday, 1	
	SIGNED BY	CHIEF OF SURVE	Y PARTY	DATE		
	APPROVED AND SIGNED	(SEAL)				
	LAKE TOWNSHIP (East Part)					
	SURVEYOR'S MICHIGAN I	REGISTRATION ?	NO	BE		i rani)