

RATIFIED BY THE BERRIEN COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990

BERRIEN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

99 AUG 16 AM 9:29

SERVANCE TRETHERWAY
 REGISTER OF DEEDS
 BERRIEN COUNTY, MICHIGAN

For corners in Berrien (County)

Located In: _____ Corner Code # _____

- 1. Public Land Survey T 8S R 20W L 9
 T _____ R _____
 T _____ R _____
 T _____ R _____
- 2. Property Controlling S _____ T _____
 in Section S _____ T _____
 3. Miscellaneous S _____ T _____
 Property in Sec. S _____ T _____
- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____ SECTION _____

08/16/99 111#9898 A99
 CORNER \$7.00
 08/16/99 111#9898 A99
 STATE REMON FEE \$2.00

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, V.J. Strebs, in a field survey on 16 June, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

CORNER NOT SET IN ORIGINAL SURVEY.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

SET CORNER ON LINE AND EQUAL DISTANCE FROM SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 24.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 4" X 3' CONCRETE MONUMENT W/B.C.R.P. BRASS CAP

- WIT TAG IN 8" ELM WEST 31.01'
- WIT TAG IN 4" BOX ELDER N 80° W 18.79'
- WIT TAG IN 4" MAPLE S 65° W 13.94'
- WIT TAG IN 8" TRIPLE MAPLE S 70° E 9.40'
- CENTER OF SECTION 24 NORTH 1012.29'

THIS POSITION NOT ESTABLISHED BY ORIGINAL GOVERNMENT SURVEYORS.

THIS MONUMENT IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE CORNER

Signed by [Signature]
 Surveyor's Michigan License No. 26469

Date 5 Aug. 1999



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
 REVISED MAY 14, 1975
 REVISED JAN., 1983
 REVISED OCT., 1995

LIBER

4 PAGE 140