

FEB 03 1999

SECTION

BRANCH COUNTY REMONUMENTATION PROGRAM  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

iber 00003 Page 0255

For corners in

<u>BRANCH COUNTY</u> QUINCY TWP	Located In:	Corner Code #
1. Public Land Survey	T <u>6</u> S R <u>5</u> W	<u>J-13</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____	_____
	T _____ R _____	_____
3. Miscellaneous	S _____	_____
	T _____ R _____	_____
Property in Sec.	S _____	_____
	T _____ R _____	_____

STATE OF MICHIGAN  
Branch County  
Recorded

12-07-1998 13:54:21

Linda Lee Morrison-Mathews  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

ACCEPTED BY THE BRANCH COUNTY  
SURVEY PEER GROUP AS THE OFFICIAL  
CORNER UNDER MICHIGAN PUBLIC ACT 345  
OF 1990 AT A MEETING HELD ON  
11-04-1998

*E.R. Reed Co. Rep.*  
**E.R. REED**

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, EDWARD W. REED, in a field survey on OCTOBER 22, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

SOUTH QUARTER CORNER, SECTION 35

A. Description of original monument and accessories and/or subsequent restoration:

1825: WM. BROOKFIELD, DEPT. SURVEYOR - CORNER SET  
1852: H. CARY, CO SURVEYOR - SURVEY

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

WITH BACKHOE, DUG LARGE HOLE, 10' X 10', FOUND POINTED STONE & BRICK FITTING FENCES EAST

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1/2" X 18" REBAR IRON WITH REMON CAP IN PLACE OF STONE IN CI-MONUMENT BOX 4" BELOW GRADE

RAILROAD TIE ANCHOR POST N 69 E 18.00'  
(NORTH 1 OF 2)

SW CORNER TEL PED N 55 W 58.07'

NAIL & WASHER S. SIDE POWER POLE N 69 W 105.45'

ALGANSEE CORNER (J-01) WEST 34.04'

C/L NORTH-SOUTH WEST 16.5'

IN CENTER OF LANE EAST

AND IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Edward W. Reed

EDWARD W, REED

Date NOV. 4, 1998

Surveyor's Michigan License No. 33985

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

