SURVEY & REMONUMENTATION

FEB 1 3 2001

SEC

BRANCH COUNTY REMONUMENTATION PROGRAM

LAND CORNER RECORDA	TION CERTIFICATE
Filing Requirement of Act	74, Mich. P.A. 1970

STATE OF MICHIGAN

ን	Filing Requirement of Act 74, Wilch. P.A. 1970	Branch Count⊬
TION		Recorded

* For corners in 12-15-2000 14:59:46 Corner Code # BRANCH COUNTY Located in: Linda Lee Morrison-Mathews ALGANSEE TWP REGISTER OF DEEDS 1. Public Land Survey T_7S R 5 W D-7 Ober 00004 Page 0140 2. Property Controlling Register of Deeds Stamp & File Number in Section 3. Miscellaneous S Property in Sec. , Recorded Plat 1 5. Private Claims 2 EDWARD W. REED , in a field survey on OCT. 21, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 5 6 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below: 8 NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate. QUARTER CORNER COMMON TO SECTIONS 17 & 20, ALGANSEE TOWNSHIP, BRANCH COUNTY, MI ACCEPTED BY THE PHANCH COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1980 AT A MEETING HELD ON 11-72-2000 A. Description of original monument and accessories and/or subsequent restoration: 1825: WM. BROOKFIELD-SURVEY, NO NOTES OF CORNER 1860: KNOWLES-SURVEY, NO NOTES OF CORNER E.R. REED, CO. REP. 1891: HAMILTON-NO NOTES 1891: HAMILTON-STONE & BRICK B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: DUG LARGE HOLE AND FOUND POINTED STONE WITH FLAGGING AROUND (BOONE?) IN CENTER OF INTERSECTION, NOT ON LINE OR MIDWAY BETWEEN SECTION CORNER ACCEPTED FOUND STONE SET 2 RAILROAD SPIKE ALONG SIDE STONE SET ½" X 18" REBAR IRON OVER STONE C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: SET ½" X 18" REBAR IRON OVER STONE DE DIENE WEST END ROAD CULVERT N25W 54.2' EAST END ROAD CULVERT 47.4' N22E FOWARD SOUTHWEST CORNER TELEPHONE PEDESTAL N46E 45.20 W REED SPIKE NORTH SIDE POWER POLE S52W 116,10 LAND NORTH EDGE STEEL CULVERT CATCH BASIN SO7E 124.46' SURVEYOR MO. AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION 33985 OF THE POSITION OF THE ORIGINAL CORNER. SED LAND SUC THE WAR

EDWARD W. REED

Signed by

Surveyor's Michigan License No 33985 THIS COPY TO FOR BRANCH OINTY DEPARTMENTAL MAN DATED: OCT. 21. 2000

OINTY DEPARTMENTY. THIS DUCE.

OINTY DEPARTMENTY. THIS DUCE.

OINTY DEPARTMENT TO BE REPRODUCE.

OPY NORM, APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14,1975

REVISED.

DEEDS FOR COPPLETION. PING PURPOSES ONLY. THIS