SURVEY & REMONUMENTATION

MAR 2 1 1997

BRANCH COUNTY REMONUMENTATION CORNER

LAND	CORNER	RECORDATION	CERTIFICATE
	COMMEN	UPCOUDM!	CENTIFICATE

171 <i>PELL</i> & J.		EN RECORDATION CEN	
For corners in COMMIS	Filing Requir	ement of Act 74, Mich.	P.A. 1970ber 00003 Page 0087
BRANCH	Located In:	Corner Code ##	"STATE OF MICHIGAN Branch County
OVID TWP.			Recorded
Public Land Survey	T 7 S R 6 W	<u>L-5</u>	15 85 155 155 155
	T R		10-30-1996 09:22:20
	<u>T</u> <u>R</u>		Linda Lee Morrison-Mathews
1 Dranate Controlling	T R		REGISTER OF DEEDS
2. Property Controlling in Section	S T R S T R		
3. Miscellaneous	S T R		Register of Deeds Stamp & File Number
Property in Sec.	S R		1.09ister of Deeds Statish & File Maniber
4 1 -4 N-	Popular Dat		
	Recorded Plat		A B C D E F G H I J K L
			2 - 6 5 4 3 2 1
			³ ┡┈┼┈┼┈┼┈┼┈┼┈┤┈┤┈┤
. ma			4 →
	in a field survey onUL\ equirements of P.A. 74, Michigan P.A.		stioned
in lines 1 and 2 above were	in conformance with regulations an	d rules therefore as required	in the
· · · · · · · · · · · · · · · · · · ·	ructions of the United States Depart a Court of Law and/or that the corne		land5 • L.
above were in conformance w	ith the rules of the Michigan Board o	Land Surveyors or by a Decr	ee of a
Court of Law; established, expressed below:	re-established, monumented, re-n	nonumented, recovered, lou	and as
·	corners, all in the same town an	d range, may be recorded	11 11 11 11 11 11
on this certificate			12 31 32 33 34 35 36
			13 1 1 1 1 1
	monument and accessories and		
	MON TO SECTIONS 12 & 13		WP., BRANCH COUNTY, MI
	LD, DEP. SURVEYOR, CORN FOUND CORNER	ER SET	
•	FOUND TWO STAKES & STA	KE HOLE, SET STONE	PIPE & STONES
	COUNTY SURVEYOR, IRON		
1973: E.R. REED, I	PLAT OF "MELODY LANE"	TIED TO CORNER	
	•		
B. Description of corner e	evidence found and/or method a	pplied in restoring or reest	tablishing corner:
FOUND 1" PIPE	_		
SET 1/2" x 18" REBA	R & REMONUMENTATION CA	P IN CAST IRON BOX	FLUSH WITH ROAD SURFACE
			EDWARD W. REED
			LAND
		•	SURVEYOR
			NO.
		•	33985
			TOED LAND SURVE
<u>-</u>			ocating the position of the corner:
	TH REMONUMENTATION CAP	IN CAST IRON BOX	
S 26.2' CONCRETE AN S54E 46.9' TO CENTE			ACCEPTED BY THE BRANCH COUNTY SURVEY PEER GROUP AS THE OFFICIAL
N60W 73.0' TO FACE			CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON
S32W 40.7' TO FACE			<u> </u>
•			le N. Keed Co. Kep.
			E.R. REED
AND IS ACCEPTED A	S A САВЕЕТИ. AND БУТИЧЕ	T. DERDENTIANTON OF	THE POSITION OF THE ORIGINAL CORN
ing to though this M	~ 11 CONTROL VIOLENTIAL	ON THE DIVITION OF	THE FOSTITON OF THE OXIGINAL COKN
	//	•	
\(\sigma \sigma \).	111 8/11		
Signed by	· 10 · 1 M	Date	JULY_20, 1996
Edward W. R Surveyor's Michigan Licens	eed / e No3398!	5	FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 11
y and wings in model to			REVISED MAY 14. 19
			marcour and 1