Date 11/25/97 18		OUNTY REMONUMENTATI	CALHOUN COUNTY RECORDED
CALHOUN COUNT REMONUMENTATIO		R RECORDATION CERTIFIC ment of Act 74, Mich. P.A.	1970 1 DEC 97 4:48 P.M.
CALHOUN  (County)  BEDFORD	Located in:	Corner Code #	ANNE B. NORLANDER CLERK - REGISTER OF DEEDS
Public Land Survey	T <u>1S</u> R <u>8W</u> TR TR	B-7	LIBER 1980 PAGE 497
2. Property Controlling S	TR TR TR		Register of Deeds Stamp & File Numbe
4. Lot No, Recorder 5. Private Claims			
I. ROBERT R. CARR  , in a field survey on <u>SEPTEMBER 29</u> , 19.97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:  NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:			t 4 7 -8 9 10 11 12 d 5 4 6 18 17 16 15 -14 13
1826 G.L.O. SYVESTER SIBLEY, D.S. SET ORIGINAL CORNER. 1888 RESURVEY BY SETH PRATT FOUND POST FROM I U.S. BEARING (STUMP) 1972 L.C.R.C. BY MILTON DEKEYSER. L. 992, P. 33.			SURVEY & REMONUMENTATION
		·	APR 0 7 1998
		n de designe en encadable	SECTION
·		applied in restoring or reestabl	isning corner:
FOUND 1/2" IRON WITH THREE DEKI DUG AND FOUND IRON PIPE WITH ACCEPTED AS TRUE PERPETUATION	I TILE BELOW AT ABOUT 4	NING FEET DEEP IN FILLED AREA.	·

Description of monument for corner and accessories established to perpetuate locating the position of the corner: C.


BERNTSEN MONUMENT IN MONUMENT BOX OVER CLAY TILE

SET BERNTSEN MONUMENT IN MONUMENT BOX OVER TILE.

SET SPOTTER IN 30" OAK, S27°W 69.83 FEET
SET SPOTTER IN 14" OAK, S41°E 52.17 FEET
SET SPOTTER IN 16" OAK, N29°W 66.18 FEET
SET SPOTTER IN UTILITY POLE, N67°W 90.28 FEET
SET SPOTTER IN 6" ASH, N20°E 44.63 FEET
CENTERLINE OF CREEK, EAST 28 FEET, MORE OR LESS

APPROVED

Signed by Surveyor's Michigan License No.\_



STATE OF MICHIGAN

FORM APPROVED BY MICHGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975