

SURVEY & REMONUMENTATION

APR 26 1995

CALHOUN COUNTY COMMISSION

APPROVED

ate 10-19-94  
CALHOUN COUNTY  
EMONUMENTATION.

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Calhoun (County)	Located In:	Corner Code #
1. Public Land Survey	T 2 S R 7 W	E-8
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

STATE OF MICHIGAN  
CALHOUN COUNTY  
RECORDED

25 OCT 94 9:02 A.M.

ANNE B. NORLANDER  
CLERK - REGISTER OF DEEDS

Register of Deeds Stamp & File Number

Donald J. Davis, in a field survey on October 21, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original survey in 1824. Resurvey in 1889 by Hodgman, tile set.

Tile found and used on Plat of Parkshores, Liber 17 of Plats, on page. 27.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found clay tile on north side of 4" concrete post.

LIBER 1773 PAGE 884

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Tile.

- 3.6' E of chain link fence.
- 12" Sassafrass S 5 ° W 9.14'
- 10" Pine N 85° W 7.05'
- 12" Pine N 40° W 10.73'
- Corner fence post N 5 ° W 16.41'.



Signed by Donald J. Davis  
Surveyor's Michigan License No. 17617

Date February 23, 1994