

APPROVED

Date 11-12-96
CALHOUN COUNTY
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

19 FEB 97 3:49 P.M.

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

LIBER 1916 PAGE 111

Register of Deeds Stamp & File Number

For corners in

Calhoun

Located in:

Corner Code -#

Newton Twp.

- | | | |
|------------------------------------|-------------------------|------------|
| 1. Public Land Survey | T <u>3S</u> R <u>7W</u> | <u>F-5</u> |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| | T _____ R _____ | _____ |
| 2. Property Controlling in Section | S _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |
| 3. Miscellaneous Property in Sec. | S _____ T _____ R _____ | _____ |
| | S _____ T _____ R _____ | _____ |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Donald J. Davis, in a field survey on October 8, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original survey by Sibley in 1826.
Resurvey by Whitney in 1897, tile set.
Tile used in 1912 by A.H.Chase.
Tile used by DeKeyser in 1989.
Tile used by Davis in 1994.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found tile and accepted as good location of original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Harrison monument.
Nail & Tag 6" x 6" railroad tie post East 47.15'
Nail & Tag Utility pole westerly power line N 60° E 3.25'
Nail & Tag Utility pole easterly powerline N 12° E 251.55'
Nail & Tag 45" Oak N 87° E 107.00'

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Newton Twp.



Signed by Donald J. Davis
Surveyor's Michigan License No. 17617

Date 2/3/97

SURVEY &
REMONUMENTATION

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1993

APR 07 1998

SECTION