

APPROVED

Date 12-9-98 KRC
CALHOUN COUNTY
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

15 DEC 1998 3:32:06 PM

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

LIBER 2087 PAGE 914

Register of Deeds Stamp & File Number

For corners in

Calhoun (County)	Located In:	Corner Code #
Leroy Township		
1. Public Land Survey	T 3 S R 8 W	F-10
	T ___ R ___	_____
	T ___ R ___	_____
	T ___ R ___	_____
2. Property Controlling in Section	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
3. Miscellaneous Property in Sec.	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, William K. Crane, in a field survey on December 3 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

This position was not established by the original government surveyors.

SURVEY &
REMONUMENTATION

MAR 30 1999

SECTION

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set corner at the intersection of the 1/4 lines.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Placed standard Calhoun County Remonumentation monument (Berntsen monument with monument box) at intersection of 1/4 lines.

Nail and tag in 15" Triple Ash	N 35° E	65.66'
Nail and tag in 30" Hickory	S 75° E	33.84'
Nail and tag in 4" Ash	N 60° W	31.12'
Nail and tag in 16" Hickory	S 10° E	128.04'

Signed by William K. Crane

Date December 9, 1998

William K. Crane, P.S.

Surveyor's Michigan License No. 29243

