

CALHOUN COUNTY REMONUMENTATION  
**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970

**APPROVED**  
 Date Sept 20 1995  
**CALHOUN COUNTY**  
**REMONUMENTATION.**

For corners in

<u>Calhoun</u> Clarendon Twp.	Located In:	Corner Code #
1. Public Land Survey	T <u>4</u> S R <u>5</u> W	<u>I-10</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

STATE OF MICHIGAN  
 CALHOUN COUNTY  
 RECORDED  
 22 SEP 95 10:04 A.M.  
 ANNE B. NORLANDER  
 Register of Deeds, State of Michigan

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Frederick J. Cutcher, in a field survey on September 18, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:  
 Original Government Survey, December 1825: W. Oak 48" S 15° W 19-1/2 lks.; Maple 10" N 22° W 19-1/2 lks.  
 S. Smith, 1977: Found R.R. spike; fence corner post East 29.25'; 32" Maple West 55.58'; 6" Sassafrass N 45° W 37.85'; ±3' West of centerline. (Calhoun County Road Commission)  
 Survey by F. Cutcher, 4/23/59: referenced to East 1/4 post; R.R. spike 3.2' West of centerline; R.R. tie fence post East 39.7'; Power Pole N 87° E 59.55'; 40" Maple West 55.6'.

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
 Found 1/2"x18" iron rod in monument box 2' West of centerline N/S road. Monument box set by Calhoun County Road Commission in the 1980's.  
 Two of the above references were found.



CALHOUN COUNTY  
 REMONUMENTATION  
 FEB 22 1996  
 COMMISSION

2. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
 Replaced 1/2"x18" iron rod with county issue Bernsten marker in monument box and is accepted as a careful and faithful reestablishment of the position of the original corner.  
 2' West of centerline N/S road.  
 In line with fence rows East and West.  
 Nail & spotter Power Pole East 59.95'.  
 Nail & spotter 18" Hickory N 80° W 34.10'.  
 Nail & spotter 12" Hickory N 52° W 37.88'.  
 Nail & spotter R.R. tie fence post S 85° E 40.00'.

LIBER 1822 PAGE 46

Signed by Frederick J. Cutcher Date September 19, 1995  
 Frederick J. Cutcher  
 Surveyor's Michigan License No. 24592