Ratified by Fear Group
In Accordance With P.A. 345

;

				រព	Nocoldatice Alm	F.A. 040	
		LAND CORNI	ER RECORDATION CER	TIFICATE C	hairman Solo	<u>L Keels</u>	-
		Filing Requir	ement of Act 74, Mich.	P.A. 1970	A CANCAL	1995 رها	-
or	corners in	CASS	COUNTY REMONUMENTAT	ŢΙΟΝ Re	corded	•	
	CASS	Located In:	Corner Code ##				
	(County) SILVER CREEK TW	IP.	·	05	i-16-1995 12:01:	10	
	Public Land Survey	т <u>5</u> в <u>16</u>	I-1	۸	l Cimmana		
	NE Con. Sec. 3	T R			m L. Simmons GISTER OF DEEDS	•	
	•	T R		, KE	GIOLEK OF NEEDO		
		. <u>T</u> R				-	
.	Property Controlling	S T R S T R				÷ .	
	in Section Miscellaneous	S T R		Regis	ster of Deeds Stamp	& File Number	
	Property in Sec.	S T R		ricgis	ster or beeds ottom		
		Recorded Plat			ABCDEF	GHJK	L M
⊃.	Private Claims		- Little		2 5 5 4 -	- -	-1-1
					3	 	
		_		-	4		-12-
	Dale L. Kesler	, in a field survey on	ebruary 10, 19 95	<u> </u>	5	- - - - - -	
10t	hereby certify that under red	quirements of P.A. 74, Michigan P.J. n conformance with regulations a	a, of 1970, the corner points me and rules therefore as required	ntioned d in the	6 18 17 16	1514	13
⊃ur	rent manual of survey instru	uctions of the United States Depa	rtment of the Interior, Bureau	of Land	7		
-Aar	nagement or by a decree of	a Court of Law and/or that the corr th the rules of the Michigan Board	er points mentioned in lines 3,	, 4 and 5	B 19 20 21-	22 23	_24—
abo Dor	ove were in conformance wi urt_of_Law;_established,_i	th the rules of the Michigan Board re-established, monumented, re	monumented, recovered, fo	ound as	9	++++	+
∋xį)	ressed below:				10 30 29 28	2726	25 I
-40		corners, all in the same town	ind range, may be recorde	ed	"	 	_
	on this certificate.	,			12 31 32 33	34 35-	3 6 -
₹.	Description of original	- South 15° Wes	st, 25 links				
	18" White Oak - South 48° East - 149 links 1877 - Amos Smith - Identified Government witnesses - Set Post - 20" White Oak, South						
	1877 - Amos Smi 50° Eas	th - Identified Gover st, 65 Links - 7" Hic	nment witnesses - kory, South 55 1/2°	Set Post West, 15	- 20" White (5 1/2 Links	Dak, South	
	1941 - Gilmore Be	each - Point of begin er and 48" long.	ning of same, Set o	concrete c	ylinder 4" in	-	•
	1976 - Michiana	Surveyons - Found con	crete monument	 (Ov	ver.)		
₃.	Description of corner of	evidence found and/or method	applied in restoring or rec	•	• •		
	Found concre	ete monument. Accept	ed concrete monumen	nt as best	t evidence of d	corner.	
			,		1 ²⁰⁷ 1 1 ²⁰⁷ 1 1 ²⁰⁷ 1 1 ²⁰⁷ 1		kin.
		·	•	l	_{_iber}	Page Li4.1	
			WAR 27 1996				
		,	SOUND BUTTONESS OF				
			OMMISSION				
		•					
C.	Description of monum	ent for corner and accessorie	s established to perpetuate	e locating the	position of the con	ner:	
	Set concrete mo	onument with aluminu Greful and faithful pe	n cap in place of	found c	oncrete monume	ent and is	
	Fence conn SW Conner Fence conn	ner post - S. 45° 00' Section 35, T4S, R16W ner post - South - 38W	W: 0.38' , West - 36.96' 63'		STRUTE	OF MICAIG DALE L. KESLER	1111
	NW Corner	2 car garage - East -	8.95		Ē★ĒLA	ND SURVEYOR +	1111
		y - N. 20° E 39.30 pole - South - 43.33'				No.	177
	rerepnone	pore - 300011 - 43.33				38117	*
	•				SE	DIAMO SURVE	
	C ^	1 11 1		~ ^		12: 333	
-	I na boar	Lakela	Date	(8) lay	7.1995		
	gned by	#38117	- Vale	4	· · · · · · · · · · · · · · · · · · ·		
Su	ırveyor's Michigan Licen	se No		FORM APPRO	VEO BY MICHIGAN STATE BOARD	OF LAND SURVEYORS, JAN REVISED MA	
						REVISED .	

War in

A - (Continued)

1987 - Wightman-Peirce, Inc. - Found Concrete monument

1989 - Wightman-Peirce, Inc. - Found concrete monument

1994 - Don Gilchrist - Found concrete monument

Liber 00002 Page 0431