

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>6</u> S., R. <u>13</u> W.	<u>G-7</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

LIBER **1** PAGE **464**

STATE OF MICHIGAN  
CASS COUNTY  
REGISTERED FOR RECORD

1976 MAY 13 PM 3 11

*[Signature]*  
REGISTER OF DEEDS  
REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, VERNON HENDERSON do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on June 27 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

6" iron pipe  
Elm 20" N23 1/2 W 83.8'  
Elm 8" N 76 1/2 W 78.8'  
CASS Co Rd Comm Records



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

6" iron pipe over LARGE stone surrounded by smaller stones

*SE Cor. 16*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

removed 6" iron pipe and place a 3/4" gas pipe and monument box  
  
PK in East Side tele pole N82°W 72.20'  
out on top of tele riser N69°-30'W 57.81  
PK in South Side tele pole N21°W 88.88

SIGNED BY Vernon Henderson DATE 5/13/76  
SURVEYOR'S MICHIGAN REGISTRATION NO. 8891 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_