LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970 CHIPPEWA CO. 2 CORNERS.

ı		LOCATED IN	- ;	CORNER CODE NUMBER	
	. PUBLIC LAND SURVEY	_ т. <u>41</u> ^{N.}	R	A-7-3, A-7	
2	. PROPERTY CONTROLL- ING IN SECTION		E ¥.		
	. MISCELLANEOUS PROPERTY IN SECTION				
4	4. LOT NO, RECORDED PLAT				
5.	PRIVATE CLAIMS	REGISTER OF DEEDS STAMP AND			
	Gerald L. Wiggins				FILING NUMBER
te B Au E A	ne corner points mentioned in li- e-established, monumented, re- ind rules therefore as required i sureau of Land Management or nd 5 above were, in a field surve a expressed below and in confor- becree of a Court of law: Description of original monu-	nes 1 and 2 aborn monumented, rec in the current ma by a decree of a by on mance with the	ve were, in a covered or re- inual of surve court of law. rules of the l	field survey on 10-12 stored as expressed below and y instructions of the United S Furthermore, that the corne 19, found, recovered, residichigan State Board of Regist ubsequent restoration:	of P.A. 74, Michigan P.A. of 1970, , 19_88_, established, I in conformance with regulations states Department of the Interior, repoints mentioned in lines 3, 4 cored, established or re-established ration for Land Surveyors or, by a
A- /- 3	Post in Stone Mound.	en Sections	24 8 19	on shore of Lake Huro.	n. Original notes call for
A -1	S.W. Section Corner 3.74 and Tamarck 6",	of Section N15°E, 2.5	18. Post 5.	set in Stone Mound w	ith OBT'S: Birch 10", S17°E
A-7-3 A-7	Corner 13,18,24,19 &	uts record. al stone mo	und. Dis	tance south to origina	g corner: il stone mound for section il stone mound for meander o Knutsen Lake fit record.
	south for the time.				
DNR ÅK	Description of monument for NUMENT PLACED AT BOTH				
	Description of monument for NUMENT PLACED AT BOTH 6" Cedar. N77°E. 1.	corner and acces		shed to perpetuate locating the	position of the corner:
	Description of monument for NUMENT PLACED AT BOTH	corner and acces CORNERS. g1 21		shed to perpetuate locating the A-7 8" Cedar, 8" Cedar, 6" Cedar,	position of the corner:
Å-7-3 Sie	Description of monument for DNUMENT PLACED AT BOTH 6" Cedar, N77°E, 1. 6" Cedar, N33°E, 3. 8" Cedar, S80°W, 22. 6" Cedar, S26°W, 22.	corner and necessors. 8' 2' 5' 05'	ssories establi	shed to perpetuate locating the A-7 8" Cedar, 8" Cedar, 6" Cedar,	position of the corner: N56°W, 11.9' N09°W, 31.3' N85°E, 23.9' S57°E, 22.7'
Å-7-3 Sid S∪	Description of monument for ONUMENT PLACED AT BOTH 6" Cedar, N77°E, 1. 6" Cedar, N33°E, 3. 8" Cedar, S80°W, 22. 6" Cedar, S26°W, 22.	corner and access CORNERS. 8' 2' 5' 05'	ssories establic	shed to perpetuate locating the A-7 8" Cedar, 8" Cedar, 6" Cedar, 8" Cedar,	position of the corner: N56°W, 11.9' N09°W, 31.3' N85°E, 23.9' S57°E, 22.7'
A-7-3 Sid SU FO	Description of monument for ONUMENT PLACED AT BOTH 6" Cedar, N77°E, 1. 6" Cedar, N33°E, 3. 8" Cedar, S80°W, 22. 6" Cedar, S26°W, 22. Gradd L. Wigney or State and United State OR STATE AND UNITED STA	corner and access CORNERS. 8' 2' 5' 05'	ssories establication of the stability o	A-7 8" Cedar, 8" Cedar, 6" Cedar, 8" Cedar, 6" Cedar, 8" Cedar,	position of the corner: N56°W, 11.9' N09°W, 31.3' N85°E, 23.9' S57°E, 22.7' 88 OF MICH.
\$10 \$10 \$0 \$10 \$10	Description of monument for ONUMENT PLACED AT BOTH 6" Cedar, N77°E, 1. 6" Cedar, N33°E, 3. 8" Cedar, S80°W, 22. 6" Cedar, S26°W, 22.	CORNERS. 8' 2' 5' 05' Language Stration No. ATES AGENCIE	ssories establication of the stability o	shed to perpetuate locating the A-7 8" Cedar, 8" Cedar, 6" Cedar, 8" Cedar,	position of the corner: N56°W, 11.9° N09°W, 31.3° N85°E, 23.9° S57°E, 22.7° 88 OF MICAN WIGGINS LAND SURVEYOR

FORM APPROVED BY MICHIGAN STATE SOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1978

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET