

# LAND CORNER RECORDATION CERTIFICATE

**FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970**

Chippewa Co.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 42 N. R. 2 E.	A-12
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO. RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Billy D. Buckler do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 7/25 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on        19      , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

**A. Description of original monument and accessories and/or subsequent restoration:**

Original  $\frac{1}{4}$  Corner, on Westside, Sec. 31, set by Austin Burt, D.S., Sept. 28, 1940.  
 Bearings were:  
 Tamarack 6" N36°W 10 lks and W. Birch 5" S61°W 20 lks

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

Found a 4" Concrete Flat monument, set by G. F. Dela Mater, R.L.S. in 1947.  
 monument had a stake in this position at that time.  
 Corner lies 27.2' North of Hwy. Center line.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

Placed 1" pipe with 4" aluminium cap at corner  
 New Bearings:  
 8" Cedar N69°E 12.3'  
 9" Cedar S12°W 12.3'  
 7" Cedar N55°W 21.6'

SIGNED BY: Billy D. Buckler  
 Billy D. Buckler

DATE: 8/2/72

SURVEYOR'S MICHIGAN REGISTRATION NO. 1327

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY: \_\_\_\_\_  
 CHIEF OF SURVEY PARTY

DATE: \_\_\_\_\_

APPROVED AND SIGNED BY: \_\_\_\_\_  
 MICHIGAN REGISTERED LAND SURVEYOR

DATE: \_\_\_\_\_

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_