

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Chippewa Co.

2 Corners.

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY.....	T. <u>42</u> N. <u>X.</u> R. <u>6</u> E. <u>X.</u>	I-5, I-7
2. PROPERTY CONTROLL- ING IN SECTION.....	T. _____ N. _____ S. _____ R. _____ E. _____ W. _____	_____
3. MISCELLANEOUS PROPERTY IN SECTION.....	T. _____ N. _____ S. _____ R. _____ E. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, David L. Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 11-2, 19 83, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- I-5 Northeast section corner of section 15. CITS : Wood Post, 10" Aspen, S74°E, 19 lks. & 8" Aspen, N70°W, 16 lks.
- I-7 Southeast section corner of section 15. CITS : Wood Post, 8" Pine, N72°E, 24 lks. & 4" Tam., S88°W, 22 lks.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- I-5 Set 1 rod north of very old fence cor. in center line of road west. Ties to fence line west and to the N. $\frac{1}{4}$ cor. of sec. 15 indicate that the fence was built on a 1 rod offset south of the sec. line to allow for the road to be built on the sec. line. Using this position the north 1/16 cor. on the east sec. line of sec. 15 also falls at a very old fence cor. according to local, long time, residents the road and fence were constructed prior to 1930.

- I-7 Re-witnessed iron rod as found. Not of record but it fits other cor. locations and occupied lines very well.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- I-5 1" pipe w/plastic RIS cap buried in center line of road. Learings: Fence Post, W/DNR tag, S9°W, 16.35' & Fence Post W/DNR Tag, S67°W, 33.8' & 7" Aspen, N3°W, 37.5' & 5" Aspen, E39°E, 32.6'.
- I-7 1" Iron. 6" W. Birch, S51°E, 15.6' & 7" W. Birch, S22°W, 36.1' & 10" W. Birch, West, 31.4' & 8" W. Birch, N41°W, 17.0'.

SIGNED BY

David L. Babbitt

DATE 11-21-83

David E. Babbitt

SURVEYOR'S MICHIGAN REGISTRATION NO. 21558

(SEAL)