

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Chippewa Co.

1 Corner

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. <u>45</u> ^{N.} S. , R. <u>1</u> ^{E.} W.	<u>C-11</u>
2. PROPERTY CONTROLLING IN SECTION_____	, T. _____, ^{N.} S. , R. _____, ^{E.} W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION_____	, T. _____, ^{N.} S. , R. _____, ^{E.} W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Billy D. Buckler, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 9/30, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:


A. Description of original monument and accessories and/or subsequent restoration:
C-11 Section Corner 29-30-31-32, set by James H. Mullet, D.S. in 1845.
Bearings were: Birch 20", N55°E, 10 lks. and Hemlock 24", S41°W, 16 lks.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
C-11 Found corner in road intersection; a 1" iron buried in black top. Found with information supplied by older employess of Kincheloe Air Force Base.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
C-11 Witnessed Corner as we found it.

Bearings: Power Pole, S22°E, 37.35' and Power Pole, N50°W, 52.20'

SIGNED BY *Billy D. Buckler* DATE 10-5-77
Billy D. Buckler



SURVEYOR'S MICHIGAN REGISTRATION NO. 8887

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____