LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74. MICH. P.A.1970 Chippews Co. 4 Corners.

	FOR CORNERS OF—:	LOCATI	LD IN -:		CORNER	CODE NUMBE	R		
	1. PUBLIC LAND SURVEY	T. <u>50</u>	_ Š., r	6 E.	C-12, C-	11, B-13,	<u>B</u> -1	1	
	2. PROPERTY CONTROLL- ING IN SECTION———	_ ,T	N. _ S., R	E. ▼.					
	3. MISCELLANEOUS PROPERTY IN SECTION	_ ,T	N. _ S., R	E:				•	
	4. LOT NO , RECO	ORDED PLA	\T				_		
	5. PRIVATE CLAIMS						_	REGISTER OF DEEDS STAM	P AND
	I, Billy D. Buckler the corner points mentioned in lin		do 1	havaba a	retifu that und			D A 54 14/1 D A	·
A1 1 (and rules therefore as required in Bureau of Land Management or land 5 above were, in a field surve as expressed below and in confort Decree of a Court of law: A. Description of original monut	the currer by a decree by on mance with	the rules	of surve	y instructions Furthermore, 19, foun dichigan State	of the Unite, that the cod, recovered, Board of Re	and ed Str orner resto egistra	in conformance with re- ates Department of the points mentioned in lir- red, established or re-est tion for Land Surveyors	gulations Interior, nes 3, 4 tablished or, by a
Bear	Corners placed by Wells . ings were:	part, D.	o. In .	1047, (ewcebr R-T	DISCEC C.	ру и	ustin Burt, D.S.	in 18
	Quarter Cor. bet. 31-	32, S. F	14 [#] .	S304E	. A lka. L	S. Pine	17.8	14", N22 ⁰ W, 22 1k:	
2-11 3-13 3-11	Sec. Cor. 29-30-31-32 South & Corner of Sec Quarter Cor. Bet. 30-	. 31, Pi 31, W. B	ne 7", irch 10	East, O", N1] od applie	39 lks. & CW, 5 lks	Pine 8", . & W. Bi	N47 Lrch	corner:	cs.
-11 -13 -11 -12 -11 -13	B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner	. 31, Pi 31, W. B e found and a Bearin one witn remains lies on	ne 7", irch 10 l/or meth g Tree, ess tre of two	Mast, 0", N11 od applie , NW of pe, S30 pine a	39 lks. & low, 5 lks d in restoring corner. OE, with stumps in	Pine 8", & W. Bi or re-establi Scribe ma scribe ma proper po	N4' irch ishing sarks orks	corner: plain. in good condition on, foundremains	
-12 -11 -13 -11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/4 C. Description of monument for a d 1" pipe with 4" alumin	of ound and a Bearing one with remains lies on the corner and thing cap	ne 7", irch 10 lor meth g Tree, ess tre of two East e pipe. accessorie at all	Mast, O", N1] od applie , NW of pe, S30 pine s edge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laid on checks hed to perpeters. New B	Pine 8", or re-establi Scribe ma scribe ma proper po ke. well wit	N4'irch ishing tarks orks orks the p	corner: plain. in good condition on, foundremains orners in area. osition of the corner:	of no
2-11 3-13 3-13 3-11 3-12 3-13 3-11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/4 C. Description of monument for a d 1" pipe with 4" alumin	of ound and a Bearing one with remains lies on the corner and thing cap	ne 7", irch 10 lor meth g Tree, ess tre of two East e pipe. accessorie at all	Mast, O", N1] od applie , NW of pe, S30 pine s edge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laid on checks hed to perpeters. New B	Pine 8", or re-establi Scribe ma scribe ma proper po ke. well wit	N4'irch ishing tarks orks orks the p	corner: plain. in good condition on, foundremains orners in area. osition of the corner:	of no
-11 -13 -11 -12 -11 -13 -11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/4 C. Description of monument for a d 1" pipe with 4" alumin	of ound and a Bearing one with remains lies on the corner and thing cap	ne 7", irch 10 lor meth g Tree, ess tre of two East e pipe. accessorie at all	Mast, O", N1] od applie , NW of pe, S30 pine s edge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laid on checks hed to perpeters. New B	Pine 8", or re-establi Scribe ma scribe ma proper po ke. well wit	N4'irch ishing tarks orks orks the p	corner: plain. in good condition on, found remains remains remains remains orition of the corner: Pine, N3°W, 41. ine, S53°E, 7 S53°W, 17.71.	of no
2-11 3-13 3-11 3-12 3-11 3-13 3-11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/a C. Description of monument for a d 1" pipe with 4" alumin 8" J. Pine, S36 E, 2 8" J. Pine, S70 W, 5 10" J. Pine, N14 W, 8" J. Pine, S57 E, 5	of found and a Bearing one with remains lies on the found and a Bearing one with remains lies on the found cap 28.3 % 5.4 % 9 24.8 % 5.7 % 8 %	ne 7", irch 10 lor meth g Tree, ess tre of two Rast e pipe. accessorie at all 7" J. Pi 8" J. Pi	East, O", N1] od applie, NW of se, S30 pine g adge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small la on checks hed to perpet rs. New B N54 E, 2 28°E, 13 N50°E, 2 64°W, 18	or re-establic Scribe mascribe	ishing tarks orks or the p	corner: plain. in good condition on, found remains rem	of no
-11 -13 -11 -13 -11 -13 -11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/a C. Description of monument for a d 1" pipe with 4" alumin 8" J. Pine, S36 E, 2 8" J. Pine, S70 W, 5 10" J. Pine, N14 W, 8" J. Pine, S57 E, 5	of found and a Bearing one with remains lies on the iron corner and hium cap 28.3 & 5.4 & 9 24.8 & 5.7 & 8	ne 7", irch 10 lor meth g Tree, ess tree of two East e pipe.	Mast, 0", N1] od applie, NW of pe, S30 pine sedge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laid on checks hed to perpeters. New B N54 E, 228 E, 13 N50°E, 264°W, 18	or re-establic Scribe mascribe	ishing tarks orks or the p	corner: plain. in good condition on, found remains orners in area. contion of the corner: Pine, N3°W, 41. ine, S53°E, 7 S53°W, 17.71.	l. of no
-11 -13 -11 -13 -11 -13 -11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/a C. Description of monument for a d 1" pipe with 4" alumin 8" J. Pine, S36 E, 2 8" J. Pine, S700W, 5 10" J. Pine, N140W, 8" J. Pine, S57 E, 5 SIGNED BY Billy D. Buckl	of found and a Bearing one with remains lies on the iron corner and fium cap 28.3 & 9.24.8 &	ne 7", irch 10 lor meth g Tree, ess tree of two East e pipe. accessorie at all 7" J. Pi 8" J. Pi 8" J. Pi	Mast, 0", N1] od applie, NW of pe, S30 pine sedge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laid on checks hed to perpeters. New B N54 E, 228 E, 13 N50°E, 264°W, 18	or re-establic Scribe mascribe	ishing tarks orks orks or the p	corner: plain. in good condition on, found remains rem	l. of no
-11 -13 -11 -13 -11 -13 -11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/a C. Description of monument for a d 1" pipe with 4" alumin 8" J. Pine, S36 E, 2 8" J. Pine, S70 W, 5 10" J. Pine, N14 W, 8" J. Pine, S57 E, 5 SIGNED BY Billy D. Buckl SURVEYOR'S MICHIGAN REGIS	orner and nium cap 28.3' & 9' 24.8' & 9' 24	ne 7", irch 10 lor meth g Tree, ess tre of two Rast e pipe. accessorie at all 7" J. Pi 8" J. Pi 8" J. Pi NO	Mast, 0", N1] od applie, NW of pe, S30 pine sedge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laion checks hed to perpeters. New B. N54 E, 220E, 13. N50°E, 13.	or re-establic Scribe mascribe	ishing tarks orks orks or the p	corner: plain. in good condition on, found remains rem	l. of no
-12 -13 -11 -13 -11 -13 -11	Sec. Cor. 29-30-31-32 South t Corner of Sec Quarter Cor. Bet. 30- B. Description of corner evidence Replaced corner from a Replaced corner from a Corner replaced from a on one stump. Corner Corner replaced at 3/4 C. Description of monument for a d 1" pipe with 4" alumin 8" J. Pine, S36 E, 2 8" J. Pine, S70°W, 5 10" J. Pine, N14°W, 8" J. Pine, S57°E, 5 SIGNED BY Billy D. Buckl SURVEYOR'S MICHIGAN REGIS FOR STATE AND UNITED STA	of found and a Bearing one with remains lies on the iron corner and hium cap 28.3 4 5.4 4 9 24.8 8 5.7 4 8 5.7 4 8 5 7	ne 7", irch 10 lor meth g Tree, ess tre of two Rast e pipe. accessorie at all 7" J. Pi 8" J. Pi 8" J. Pi NO	Mast, NI od applie, NW of se, S30 pine sedge of Positi	39 lks. & W, 5 lks d in restoring corner. E, with stumps in small laion checks hed to perpeters. New B. 154 E, 22 28 E, 13 150 E, 164 W, 18	or re-establic Scribe mascribe	N4' rch shing tarks orks orks or the p	corner: plain. in good condition on, found remains rem	of no