LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Chippewa	Located In:	Corner Code #		1:
(County)				
1. Public Land Survey	TR TR			
2. Property Controlling in Section	S 27 T 50N R 7	W 3 W 4	: : :	
3. Miscellaneous Property in Sec.	S T R		Register of Dee	eds Stamp & File Number
4. Lot No. , Red 5. Private Claims	corded Plat	MENTAL ALL ALL ALL ALL ALL ALL ALL ALL ALL	A B C D E	·
	3	10/30/2008	2 - 6 - 5	
, Stephan J. Szyszkoski , i		10/29/2008 do hereby state	3 4 7 8	9-10-11-12-
above were in conformance with	regulations and rules therefore as	corner points mentioned in lines 1 and 2 serequired in the current manual of survey	, 5	16 15 14 13
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7				
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, 8 19 re-established, monumented, recovered, found as expressed below:			, 8 -19 -20	
To established, monumented, recov	ered, round as expressed below.		9 10 30 29	28 27 26 25
NOTE: Not more than 2 corn	ners, all in the same town and	range, may be recorded	11	
on this certificate.			12 31 32	_33343536
A. Description of original m	nonument and accessories ar	nd/or subsequent restoration:	13	
(3-Sec. 27) North 1/1	6 corner between Sect	tions 27 and 28. Not estab	blished in the	original survey.

- (4-Sec. 27) Northwest 1/16 corner, Section 27. Not established in the original survey.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (3-Sec. 27) Established the corner midway and on the Section line between Section corner 1323.07' north and Quarter corner 1323.07' south.
- (4-Sec. 27) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. (4) Set 5/8"x24" rebar with plastic MDNR cap. Set measuring nail with MDNR tag in the side of: Set measuring nail with MDNR tag in the side of: 5" J.Pine N40W 13.19' mrkd "N1/16 BT" 7" Oak \$33W 31.7' mrkd "NW1/16 BT" 8" J.Pine S27W 15.89' 12" J.Pine S57W 65.83' do do 6" J.Pine S35E 20.03' do 5" J.Pine N61W 49.95' do 6" J.Pine N43E 13.91' 5" W.Birch S56E 25.11' do dο Bearings are magnetic. Bearings are magnetic.

Signed by Surveyor's Michigan License No.

33986

11/18/2008

For the Michigan Department of Natural Resources, Office of Land and Facilities

ZYSZKOSK LAND SURVEYOR

LAND S

FORM APPROVED BY MICHIGAN STATE BOARD

47176

47177

sed Jan., 1983