LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. $18 \stackrel{N.}{\bullet}$, R. $06 \stackrel{\emptyset}{w}$.	C-3 ^L	
2. PROPERTY CONTROLLING IN SECTION 5	,T. 18 N. R. 06 W.	1, 8, 11	
3. MISCELLANEOUS PROPERTY IN SECTION	,T N. R E.		
4. LOT NO, RECOR	DED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
I, CARL F. ROSER	, do hereby c	ertify that under requirements o	of P.A. 74, Michigan P.A. of 1970,
the corner points mentioned in line re-established, monumented, re-mo and rules therefore as required in Bureau of Land Management or by and 5 above were, in a field survey as expressed below and in conform Decree of a Court of law:	s 1 and 2 above were, in a commented, recovered or re the current manual of survey a decree of a court of law.	field survey on <u>JANUARY 3</u> stored as expressed below and by instructions of the United S. Furthermore, that the corner 19, found, recovered, rest	1 , 1985 , established, in conformance with regulations tates Department of the Interior, points mentioned in lines 3, 4 cored, established or re-established
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	K XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	жинких химиних	;
11 FD 5/8" IR ROD W/RLS CAP; ADDED CED POST W/LOC TAG. 9" BALSAM N30°W 9.5 2" BL CHERRY S30°E 23.5 4' B OAK S05°E 26.4 8" B OAK S65°W 6.8	t t		
 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: C-3 FD 1 1/4" PIPE IN OLD 4" TILE FOR SE COR OF SEC 6. FITS MCCLUNG WITS. 1 ESTAB NE COR OF NW 1/4 OF NW 1/4 OF SEC 5 PER STD B.L.M. INSTRUCTIONS. 8 FD & ACCEPTED 5/8" ROD BY RLS, MATT MCCLUNG FOR NW COR OF E 1/2 - SW 1/4 OF SEC 5. FITS STD SEC SUB'N. 11 FD & ACCEPTED 5/8" ROD BY RLS, MATT MCCLUNG FOR CTR OF SW 1/4 OF SEC 5. FITS STD SEC SUB'N. 			
C. Description of monument for e	orner and accessories estable	ished to perpetuate locating the	position of the corner:
C-3 FD 1 1/4" GALV PIPE IN 4"	1 SET 5/8" V 71:11 D	EDOD W/ ED E/9! ID	8 POD W/DIS CAD.
TILE: ADDED RLS CAP & CED	RLS CAP: & CFD	POST ADDED CED I	POST W/LOC TAG.
POST W/LOC TAG. 8" HEMLOCK NO5°E 7.6'	W/LOC TAG. 5" MAPLE SO5°E	2" OAK 10.9' 2" MAPLE	\$50°E 33.81 \$25°W 25.01
5" CEDAR N55°E 16.8' 10" HEMLOCK S35°E 4.9'	7" MAPLE N50°E	36.6' 3" BALSAM	S70°W 8.7'
10" HEMLOCK \$35°E 4.9"	8" B.OAK N40°W E-W RAND DUE N	26.0'	of Mickey
1 . 5			A CONTRACTOR OF THE PARTY OF TH
SIGNED BY Carl 7.1	•		
SURVEYOR'S MICHIGAN REGIS	TRATION NO. 1202	28	SURVEYOR NO. 12028
SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SURVEYOR SURVEYOR SURVEYOR SURVEYOR AND SURVEYOR LAND SURVEYOR LAND SURVEYOR			
SIGNED BY	CHIEF OF SIRVEY BIRTY	DATE	
APPROVED AND SIGNED BY			
	MICHIGAN REGI s tered La	ND BURVEYOR	(SEAL)
SURVEYOR'S MICHIGAN REGISTRATION NO. FREEMAN TWP. CLARE COUNTY			

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975