LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 19 N., R. 6 W.	K-2, L-2
2. PROPERTY CONTROLLING IN SECTION 1	,T. 19 N., R. 6 W.	7, 8
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 3, 19 76, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-2 Set corner at intersection of old fences E-W and N, which seems to fit U.S. notes and lines of occupation. Best evidence of proper location.

L-2 Set at calculated intersection of true ¼ lines.

7 Set by standard survey procedure for the subdivision of sections.

8 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-2

Set DNR mon. & red-top post

4" R. Pine	S88°E	56.25
4" R. Pine	S47°E	57.5

L-2

Set 3/8" hex rod & post

23" W. Pine	N10°E	84.2
5" Oak	N64°E	61.6

7

Set 3/8" hex rod & red-top post

4" R. Pine	N82°W	53.9
7" Oak	S47°W	11.6

8

Set 3/8" hex rod & red-top post

5" W. Pine	S75°W	15.85
12" R. Pine	S33°E	79.1

SIGNED BY Kenneth J Ostling DATE 12-15-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

(SEAL) STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. 10068 REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CLARE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET