LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N., R. 6 W.	M-1, M-2, M-3
2. PROPERTY CONTROLLING IN SECTION 1	,T. 19 N., R. 6 W.	14
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 2, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-1 Found 2" pipe as restored by M. Schaaf in 1941 survey in T20-5W. Fits US notes west.

M-2 Recovered corner as established by M. Schaaf in 1941 survey of T20-5W, from his witnesses.

M-3 Set corner in center of N-S township grade road, in line with old fence east and trail road west. Corner falls in cut section so any previous evidence destroyed.

14 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-1

Set DNR mon. in place of 2" pipe & red-top post

6" R. Pine	N20°E	20.45
6" R. Oak	S32°E	24.8
4" J. Pine	S46°W	5.0

M-2

Set DNR mon. & red-top post

3" W. Pine	N40°E	25.25
9" R. Oak	S43°E	28.2

14

Set 3/8" hex rod & red-top post

14" Oak	N49°W	18.4
5" R. Pine	S62°W	12.15

M-3

Set DNR Monument

5" R. Pine	N45°E	30.55
14" R. Pine	N56°W	15.5

SIGNED BY Kenneth J. Ostling DATE 12-15-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

STATE OF MICHIGAN (SEAL) KENNETH J. OSTLING LAND SURVEYOR No. 10068 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CLARE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET