LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
	1. PUBLIC LAND SURVEY	T. 19 N. R. 6	A-7; B-7; B-8	-
-				
	3. MISCELLANEOUS PROPERTY IN SECTION	,T S., R W		
	4. LOT NO, RECORDED PLAT			
	5. PRIVATE CLAIMS		· · · · · · · · · · · · · · · · · · ·	REGISTER OF DEEDS STAMP AND FILING NUMBER
c.	I, Carl F. Roser			
	Fd 2" pipe; drove 1" pipe w/DNR cap			
	inside 6" Ta 2" Wh 12" Ta 23" Wh Edge o	pipe; drove 1" p & set cedar pos mrack West ite Pine N80° mrack S20° ite Pine N40° f Marsh East f Marsh Nort	14.44' E 29.3' W 130.4' E 189' 265'± 10'	;
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: Fd 2" Schaaf pipe that fits 3 Schaaf NBT's. Schaaf notes (Jan. 1940) indicate he had original evidence here. Corner has been used by RLS, J. Sedgman. 1" pipe with DNR cap is 8' long in leather leaf marsh. B-7 - Fd & accepted ½" rod by RLS, J. Sedgman (S.P. to U.S.) for N½ Cor. of Sec. 19. No evidence of Schaaf pipe or his NBT's. Fd smooth wire on tree's (E&S), 73'± N & 18'± E. B-8 - Established center of Section 19 at intersection of 1/4 lines.				
	C. Description of monument for B-8			·
set 18" 10" 8"	ve 5/8"X34" re-rod ced post w/loc tag Black Oak N25°E Black Oak S35°E Red Pine S15°W N-S dirt rd Due W	27.1' 55.0' 40.6'	11" Black Oak 15" Black Oak 10" Black Oak Set ced post w/loc tag	N25°E 59.88' Due E 65.13' S35°W 58.77' Due E 33'
	0 15	Ω	Ctr N-S rd	11111111111111111111111111111111111111
	SIGNED BY Carl 7.1	JOSED 01-06	DATE	CARL
	SURVEYOR'S MICHIGAN REC	SISTRATION NO	12028	F. ROSER (SELL) LAND SURVEYOR
	FOR STATE AND UNITED ST	TATES AGENCIES:		0 No. 12029
	SIGNED BY	CHIEF OF SURVEY PARTY	DATE	LAND SURLEY
		MICHIGAN REGISTERED	LAND SURVEYOR	(BEAL) REDDING TWP
	SURVEYOR'S MICHIGAN REC			CLARE COUNTY