LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. S., R. 6 E. W.	G-7;H-7;I-7;I-9
2. PROPERTY CONTROLLING IN SECTION	T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 25, 19 85, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

I-7

Fd 1" pipe in mon box in ctr E-W bit. road

Power Pole	S20°W	196.10'
9" Black Oak	N50°W	128.65'
Set ced post w/loc tag	S45°W	66'

I-9

Found 3/4" iron rod w/RLS cap

16" Cedar	N50°W	65.54'
8" Cherry	N15°E	87.03'
Power Pole	N60°E	32.69'
Set ced post w/loc tag	East	16.5'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G-7 - Fd & accepted 1" pipe for NW Cor. of Sec. 22. Fits M.S.H.D. and Paul Lapham witnesses.

H-7 - Fd 3/4" pipe for N¼ Cor. of Sec.22. Pipe is buried 3" in old E-W gravel road. Fits M.S.H.D. and Paul Lapham witnesses.

I-7 - Found 1" pipe in monument box for NE corner of Section 22.

I-9 - Fd 3/4" iron rod with RLS, M. McClung cap; in approx. Intersection of dirt roads N-S-W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7

Found 1" pipe

11" Jack Pine	S70°W	63.89'
Power Pole	N35°E	33.00'
Power Pole	S65°E	78.44'
14" Oak	S20°E	84.11'
Fd 5/8" iron rod in approx. ctr. st. intersection	N44°23'E	5.26'

H-7

Found 3/4" pipe

7" Black Oak	N70°E	79.94'
Power Pole	S10°E	62.60'
Conc & stone masonry post	Due S	30.1'

SIGNED BY Carl F. Roser 01-06-86 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

REDDING TWP
CLARE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

Reproduced by the State of Michigan