LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. ●, R. 6 ● W.	B-9; A-9
2. PROPERTY CONTROLLING IN SECTION	T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 11, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

B-9

Fd well pt. w/RLS cap & added cedar post w/loc tag

*12" Oak stp, 1½' high	N60°W	23.26'
Schaaf pipe	N2°53'W	42.25'
17" Oak	S85°E	30.25'
*21" Oak	S60°W	32.18'
Ctr N-S sand rd	West	80'± 1'

* = G. DeLaMater & J. Sedgman Wit's.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-9 - Fd old well point for 1/4 Cor. common to Sec's 19 & 30; for perpetuation of Milton Nye's June 1857 correction to Francis Coleman's 1856 corner. This point (Nye's) has been used by RLS, J. Sedgman and RLS, Glen DeLaMater. Marcus Schaaf's 1½" pipe (& two NBT's) as set Aug. 1939; is N2°53'W, 42.25', (drove flush).

A-9 - Fd & accepted 3/4" pipe in 3" clay tile as recovered by RLS, Dan Schripsema in 1982 for SW Cor. of Sec. 19. RLS, McClung moved his Osceola Co. mon. to this position in fall, 1982. A Schaaf position (1939) from his NBT remains would be 8.5'± S & 2'± W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-9

Fd 3/4" pipe in 3" clay tile (buried 2")
Fd Osc. Co. mon buried 6" on E side tile

16" Black Oak	N50°W	47.07'
17" Black Oak	N30"E	34.78'
10" Jack Pine	S40°W	46.07'
Set Ced Post w/loc tag beside fd ½" iron rod w/RLS cap	Due N	33.00'
Fd 2"x2"X¼" angle iron	N57°W	5.2'
Ctr E-W road	Due N	2'

SIGNED BY Carl F. Roser 01-06-86 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

REDDING TWP
CLARE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET