## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

F	OR CORNERS OF -:	LOCATED IN -:	0	ORNER COD	E NUMBER	1	
ı	. PUBLIC LAND SURVEY	T. 19 N., R. 6	_ w: I-	8; H-9;	G-9		
2	PROPERTY CONTROLL- ING IN SECTION———	,T N	F				
3	MISCELLANEOUS PROPERTY IN SECTION	,T N. S., R	E.				
4	. LOT NO , RECO	RDED PLAT					
5	. PRIVATE CLAIMS						OF DEEDS STAMP AND
ī.	Carl F. Roser	do here	hy certify	that moder a	reavisements a	TPA 74	Michigan P.A. of 1970,
re a E a a	he corner points mentioned in line- e-established, monumented, re-mand rules therefore as required in  Bureau of Land Management or band 5 above were, in a field survey  as expressed below and in conformations.	es 1 and 2 above were, commented, recovered the current manual of by a decree of a court of y on	in a field or restored survey in: [ law. Fu , 19	survey on l as express structions of thermore, th , found, r	ed below and the United S nat the corner recovered, rest	in confortates Departments moints mored, estal	, 19 3, established, mance with regulations ortment of the Interior, entioned in lines 3, 4 dished or re-established
c. t	Decree of a Court of law: Continued:						
4	К.Х. Язимарскох вежнодожей жэсэсэс		kxxxkx:	KOCH DOK SKOK	XXXX		:
	Found	G-9 1" sucker roa	ad				į
	Power	Pole	N	20°E	111.05'		
	12" C Set c	edar ed post	S	50°E	90.70'		
		c tag	s	45°E	66'		
		tr of W end 30		30°W	E1 21		
	CMP : Ctr N	x-culv -S bit rd			51.2' 15'		
- oB	Ctr N Ctr d Description of corner evidence - Fd 3/4 re-rod &	irt rd E'ly found and or method	applied in	ue S restoring or	<b>2 </b> ⊤re-establishin	g corner:	i
1-8	M.S.H.D. wits. and	Stones in app	Prox.	ctrofi	N-S dirt	road.	Fits 3
	In line with fence	to East per N	1.S.H.	D. (1967	7).		
<u>H-9</u>	- Fd 2" pipe with	RLS, M.McClund	cap.	in appro	ox. ctr	of E-W	dirt road.
G-9	Fits Paul Lapham w - Fd 1" sucker rod	ltS. that fits Pau	ıl Lani	nam wite	s and o	F Ri+	surface
	road (gravel south	of here) is 3	33'± s	outh.	o. end o.	DIC.	Surruce
C	. Description of monument for	corner and accessories	etablichad	ta normatual	to kveitina tho	position of	the corner
	1-8				H-9	position of	t the corner.
31"	3/4" re-rod and stor	nes W 37.32!	Foui	nd 2" pi	ipe	50F	30 05!
10"	Black Oak N50° White Pine S50° fn's E&S Due	W 100.04'	10 <b>"</b>	Red Pir	ne S	15°W	38.85' 51.64'
Cor	fn's E&S Due 1	E 301					
w/1	ced post loc tag Due 1	w 33'	W/	loc tag	Du	ie N	33'
Ctr	N-S dirt rd Due	E 2'					
							ALLE OF MICKE
	0 1-5			_		Š	A
S	IGNED BY Cal 7.	Your 01	-06	86 n	ATE	, i	CARL 2
							LAND *
S	URVEYOR'S MICHIGAN REG	ISTRATION NO	2028	<del></del>		3	No. 12028
	OR STATE AND UNITED STA					•	CALO LAND SURTIN
S	IGNED BY	CHIEF OF SURVEY PARTY		D	ATE		
	PPROVED AND SIGNED BY_						
		MICHIGAN REGIBTES	RED LAND SU	RVEYOR		15	EAL)
					nı	መስተልድ ፣	'LID
s	URVEYOR'S MICHIGAN REG	ISTRATION NO.				EDDING T Lare Co	
_							STRATION, JAN. 28, 1971