LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LOCATED IN -:

FOR CORNERS OF -:

CORNER CODE NUMBER

	1. PUBLIC LAN	D SURVEY	т. 19	N. ●., R	06 ₩:					
	2. PROPERTY O	CONTROLL 0	6 ,T. <u>19</u>	N. ●., R	06 🕷	13, 14, 16				
					1					
	4. LOT NO. , RECORDED PLAT									
	5. PRIVATE CL.	AIMS			-				DEEDS STAMP AN G NUMBER	D
	the corner points re-established, n and rules therefore Bureau of Land and 5 above wer as expressed bel Decree of a Cou C. (CONTINUE	s mentioned in line in the conumented, re- tore as required in Management or its in a field survition and in confourt of law: ED)	mes 1 and 2 monumented, in the current by a decree ey on rmance with	above was recoved to manual of a country the rule	red or red or red or red or red of survert of law.	rtify that under required survey on stored as expressed y instructions of the Furthermore, that 19, found, reconfichigan State Board	below and in the United State the corner povered, restored of Registrates	22, 19 n conformance tes Departmentic points menticed, established ion for Land	9 86, established with regulations of the Interpolation lines 3 and or re-established or, but the surveyors or	ned, ions rior, B, 4 hed
	5/8" X 34" K LOC TAG.	KE-KOD W/KLS	CAP & CE	בט פט		DROVE 5/8" POWER POLE	-		S CAP. 52.68	
2" B	CHERRY	N15°E	20.5			12" B. CHEF	RRY	N50°E	42.00	
-	APLE APLE	S50°W S80°W	20.4 49.6			9" R. PINE CTR LINE E-			47.82 4'	
4" 14	PV LE	200-M	77.0			SET RR TIE			33 '	
						TAG.			·	
 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: C-3 FD 7 ACCEPTED 3/4" ROD & IRON BAR FOR SE COR OF SEC. 6. CORNER IS IN LINE WITH OLD FN REMAINS NORTH. COR FITS ONE M. SCHAAF N.B.T. REMAINS. 13 ESTAB. CTR. OF SE 1/4 OF SEC. 6 PER STD. B.L.M. INSTRUCTIONS. AN OLD FN COR (W-W FN'S) 										
14 16	N-S-E-W, DOWN) IS 13'± S. AND 10'± E. 4 ESTAB. THE SE COR OF NE 1/4 OF THE SE 1/4 OF SEC. 6 PER STD. B.L.M. INSTRUCTIONS. CTR OF OLD OVER-GROWN N-S GRADE (14' BETWEEN DITCHES) IS 3'± EAST.									
							v . a .	. w ca.		
ווא א	ACCEPTED 3/ THORNAPPLE OAK ELM R LINE E-W [T CED POST V	/4 ROD W/1/2	X N15 ⁹ F	2" BAR 39.	ON E. 5	shed to perpetuate li SIDE (BURIED 41	") SET 5 & C 8" M 5" M	/8 X 34" ¹ ED.POST W APLE S65	3 RE-ROD W/R. V/LOC. TAG. °W 30.7 °E 25.8	•
	s., P.LAPH							.45	OF MICH	
	SIGNED BY	Parl 7.	Roser	01-	27-8	26 DAT	`E		CARL F. ROSER	
	SURVEYOR'S M	MICHIGAN REG	CISTRATION	NO	12028				LAND SURVEYOR .	80
	FOR STATE A							% ° 0 x −	12028 SVR	ritis.
	SIGNED BY				<u>. </u>	DAT	E		PED LAND SUR	_ _
	APPROVED AND SIGNED BY									
								EDDING TWP. LARE COUNTY		
	SURVEYOR'S MICHIGAN REGISTRATION NO								ſ	
	CONTENCTOR	alomoan ne	JULIALIO	· 110						

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975