

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____ N. <input checked="" type="checkbox"/> S., R. _____ E. <input checked="" type="checkbox"/> W.		
2. PROPERTY CONTROLLING IN SECTION <u>28</u> T. <u>19</u> N. <input checked="" type="checkbox"/> S., R. <u>6</u> E. <input checked="" type="checkbox"/> W.		5;10
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ S., R. _____ E. _____ W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 6, 19 85, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
5 - Estab. SE cor of N $\frac{1}{2}$ of NW $\frac{1}{4}$ of S-28 per Std. B.L.M. instructions.

10 - Established S $\frac{1}{8}$ corner on Sec. line common to secs 28 & 29 mid-way & on line between fd W $\frac{1}{4}$ cor & SW cor of Sec. 28 (recovered Schaaf cors). A Schaaf 2" pipe set in error in 1940 - for 1/8 cor is S17 $^{\circ}$ W, 11.6'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

	<u>5</u>		<u>10</u>		
Set 5/8" x 34" rerod w/RLS cap & ced post w/loc tag			Drove 5/8" x 34" rerod w/RLS cap & cedar post w/loc tag		
8" Maple N40 $^{\circ}$ W	19.3'		9" B oak N40 $^{\circ}$ W	17.2'	
7" Maple N60 $^{\circ}$ E	10.0'		12" B. oak S35 $^{\circ}$ E	14.8'	
4" Maple S25 $^{\circ}$ E	3.6'		12" B Oak S45 $^{\circ}$ W	29.4'	


SIGNED BY Carl F. Roser 01-06-86 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. _____

REDDING TWP.
CLARE COUNTY

Reproduced by the State of Michigan