LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

		-: co	RNER CODE N			
. PUBLIC LAND SURVEY	T. 19 %.	R6 ¥D-	-10;			
PROPERTY CONTROLL- 1	29 ,T. 19 §.,	R. 6 %. 4;	5;8			
MISCELLANEOUS PROPERTY IN SECTION -						
LOT NO , R						
PRIVATE CLAIMS				REGIS	STER OF DEEDS STAM FILING NUMBER	P AND
Cowl F Boson	<u>.</u>	, do hereby certify	that mudar ram	irements of PA	74 Michigan P.A.	of 1970,
a comer mainte mantioned	in lines 1 and 2 abo	ve were, in a field :	survey on <u> </u>	ebruary 13	, 19 <u>_85</u> _, est	ablished,
astablished manumented	re-monumented te	covered or restored	as expressed	below and in co	mormance with re	Bararions
nd miles therefore as requir	ed in the current m	anual of survey inst	tructions of the	· United States 1	Department of the	interior,
fureau of Land Management and 5 above were, in a field s	t or by a decree of	a court of law. Furt	thermore, that	the corner point	ts mentioned in its established or re-es	tablished
nd 5 above were, in a field s s expressed below and in co	survey on onformance with the	rules of the Michig	gan State Board	l of Registration	for Land Surveyors	or, by a:
Decree of a Court of law:			-			
C. CONTINUED		11 .		***		
жжидтохускогорунжайску: 5	KKM HISTKRIKK KOKK	SHUOSSCHRIK RIK RIKRA	KEKKHEKHIKANI K	юх <u>8</u>		i
)rove 5/8" x 34" re	-rod w/R.L.S.	cap: Dro	ve 5/8" x 3	34" re-rod w	/R.L.S. cap	•
et cedar post w/lo	c tag	set	ced post v			
.1" Oak \$40°	E 36.7			S55°E	46.0'	
8" oak \$65°: .6" oak \$60°:	E 23.8			SO5 ^o E S40 ^o W	31.7' 30.7'	
.6" oak S60 ⁰ dge of N-S East	•	=	Oak Ir w/RLS	N89°36'W	10.28	
.dge of N-5 East Bluff	37	ca		1107 30 11	20,20	
		Fd	Schaaf Pip	e S18 ⁰ 40'W	22.9	
•	م/ انظم المستمال و الك	a mathad applied in	voctoring or re	s actablishing corn	mr.	
<u>D-10</u> - Estab. ctr of N <u>4 - Estab. ctr of N</u> 5 - Establish N1/8	of Sec. 29 at Wax of Sec. 29	intersection (NW corner of	of % lines Govt lot	7) per std B	.L.M. instruc	tions
D-10 - Estab. ctr of N - Estab. ctr of N - Establish N1/8 N cor of S-29.	of Sec. 29 at W½ of Sec. 29 cor on N-S ½ 1 ner on E-W½ 1	intersection (NW corner of Line of Sec. 2 Lne of Sec. 29	Govt lot 9 midway a	7) per std B nd on line b	.L.M. instruc etween Ctr &	
8 - Estab. W1/8 cor line between W2	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk 11 cor & ctr of	intersection (NW corner of line of Sec. 2 lne of Sec. 29 Sec. 29.	Govt lot g midway a (NW corne	. 7) per std B nd on line b r of Govt Lo locating the posit	i.L.M. instructed tween Ctr & it 8) midway & ion of the corner:	on
-10 - Estab. ctr of N - Establish N1/8 N½ cor of S-29. 3 - Estab. W1/8 cor line between W½	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk 11 cor & ctr of	intersection (NW corner of line of Sec. 2 lne of Sec. 29 Sec. 29.	Govt lot g midway a (NW corne	. 7) per std B nd on line b r of Govt Lo locating the posit	i.L.M. instructed tween Ctr & it 8) midway & ion of the corner:	on
D-10 - Estab. ctr of No Establish N1/8 N\(\) cor of S-29. 3 - Estab. W1/8 cor line between W\(\) 2. Description of monumer \(\) 2. Description of monumer \(\) 3 - 10 4 Orove 5/8" x 34" re	of Sec. 29 at Wk of Sec. 29 cor on N-S k 1 ner on E-Wk 1i cor & ctr of other for corner and actrod w/RLS cap	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29.	Govt lot 9 midway a (NW corne to perpetuate	of per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w	i.L.M. instruction of the corner: of R.L.S. cap;	on
-10 - Estab. ctr of N - Establish N1/8 - N½ cor of S-29 Estab. W1/8 cor - line between W½ - Description of monumer - D-10 - rove 5/8" x 34" re - set ced post w/10	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk liner or & ctr of the corner and acrod w/RLS cap c tag N40°W 10.8	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29.	Govt lot 9 midway a (NW corne to perpetuate	of per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w	i.L.M. instruction of the corner: 7/R.L.S. cap;	on
D-10 - Estab. ctr of N - Establish N1/8 N\ cor of S-29. - Estab. W1/8 cor line between W\ D-10 Drove 5/8" x 34" re set ced post w/lo	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk liner or & ctr of the corner and acrod w/RLS cap c tag N40°W 10.8	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29.	Govt lot 9 midway a (NW corne to perpetuate	of per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w	i.L.M. instruction of the corner: 7/R.L.S. cap;	on
-10 - Estab. ctr of N - Establish N1/8 N½ cor of S-29 Estab. W1/8 cor line between W½ Description of monumer D-10 rove 5/8" x 34" re set ced post w/lo	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk liner or & ctr of the corner and acrod w/RLS cap c tag N40°W 10.8	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29.	Govt lot 9 midway a (NW corne to perpetuate	of per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w	i.L.M. instructed when Ctr & st 8) midway & st 8) midway & st 8, cap; 37.2' 30.2' 53.9'	on
D-10 - Estab. ctr of No. 1 - Estab. ctr of No. 2 - Establish N1/8 No. 2 cor of S-29. B - Estab. W1/8 cor of Inne between W2. Description of monumer D-10 Prove 5/8" x 34" recompled to sugar maple of	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk liner of corner and acrod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265°	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established proced 20 10" 14" E-W	Govt lot Govt lot midway a (NW corne to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd	of per std B and on line be a few the position of Govt Locating the position of Gove Locating the position of Gove Lag N60°W N70°E S35°W South	i.L.M. instruction of the corner: 7/R.L.S. cap;	on
D-10 - Estab. ctr of No. 1 - Establish N1/8 N½ cor of S-29. B - Establish W1/8 cor of S-29. B - Estab. W1/8 cor of Inne between W½ D-10 Drove 5/8" x 34" results a set ced post w/10 cor of sugar maple cor sugar	of Sec. 29 at Wk of Sec. 29 cor on N-S k liner on E-Wk liner of corner and acrod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265°	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established proced 20 10" 14" E-W	Govt lot 9 midway a (NW corne to perpetuate	of per std B and on line be a few the position of Govt Locating the position of Gove Locating the position of Gove Lag N60°W N70°E S35°W South	i.L.M. instruction of the corner: 7/R.L.S. cap; 37.2' 30.2' 53.9' 12'	on
Description of monumer D-10 Description of monumer D-10 Drove 5/8" x 34" rest ced post w/lo set ced post w/lo sugar maple sugar maple sugar maple edge Mu Rv description of monumer D-10 description of monumer D-	of Sec. 29 at Wk of Sec. 29 cor on N-S k 1 ner on E-Wk 11 cor & ctr of other corner and acrod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265' Due N 310'	intersection (NW corner of line of Sec. 29) Line of Sec. 29 Sec. 29. cessories established proced 20 10" 14" E-W Fd	of % lines Govt lot 9 midway as (NW cornes to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir	or of Govt Lost Incating the posit 4 34" re-rod was tag N60°W N70°E S35°W South West	i.L.M. instructed when Ctr & structure at 8) midway & structure at 8) m	on
Description of monumer D-10 Description of monumer D-10 Drove 5/8" x 34" resisted agar maple sugar maple sugar maple edge Mu Rv description of monumer D-10 description of monumer D-10	of Sec. 29 at Wk of Sec. 29 cor on N-S k 1 ner on E-Wk 11 cor & ctr of other corner and acrod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265' Due N 310'	intersection (NW corner of line of Sec. 29) Line of Sec. 29 Sec. 29. cessories established proced 20 10" 14" E-W Fd	of % lines Govt lot 9 midway as (NW cornes to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir	or of Govt Lost Incating the posit 4 34" re-rod was tag N60°W N70°E S35°W South West	i.L.M. instructed when Ctr & structure at 8) midway & structure at 8) m	on
-10 - Estab. ctr of N - Estab. ctr of N - Establish N1/8 N cor of S-29 Estab. W1/8 cor line between W - D-10 - Drove 5/8" x 34" re - set ced post w/lo - " sugar maple	of Sec. 29 at Wk of Sec. 29 cor on N-S k 1 ner on E-Wk 11 cor & ctr of other corner and act of the core of the cor	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established Dro ced 20 10" 14" E-W Fd	Govt lot Govt lot midway and (NW corner to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir DA	7) per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w c tag N60°W N70°E S35°W South West	in of the corner: 7/R.L.S. cap; 37.2' 30.2' 53.9' 12' 5.6'	on set
D-10 - Estab. ctr of No. 1 - Establish N1/8 N½ cor of S-29. B - Establish W1/8 cor of S-29. B - Estab. W1/8 cor of Inne between W½ Description of monumer D-10 Drove 5/8" x 34" rest ced post w/lost sugar maple of	of Sec. 29 at Wk of Sec. 29 cor on N-S k 1 ner on E-Wk 11 cor & ctr of other corner and act of the core of the cor	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established Dro ced 20 10" 14" E-W Fd	Govt lot Govt lot midway and (NW corner to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir DA	7) per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w c tag N60°W N70°E S35°W South West	i.L.M. instructed when Ctr & structure at 8) midway & structure at 8) m	on set
D-10 - Estab. ctr of No. 1 - Establish N1/8 N½ cor of S-29. B - Establish N1/8 cor of S-29. B - Estab. W1/8 cor line between W½ Description of monumer D-10 Drove 5/8" x 34" results agar maple set ced post w/lost sugar maple "sugar maple 12" swp oak E edge Mu Rv Sedge Mu Rv Signed By Surveyor's Michigan For State and Unite	of Sec. 29 at Wk of Sec. 29 cor on N-S k I ner on E-Wk 11 cor & ctr of other corner and acrod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265' Due N 310' REGISTRATION CD STATES AGEN	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established Dro ced 20 10" 14" E-W Fd NO. 12028 CIES:	Govt lot 9 midway as (NW corner to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir DA	7) per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w c tag N60°W N70°E S35°W South West	ion of the corner: 7/R.L.S. cap; 37.2' 30.2' 53.9' 12' 5.6' CARL F. ROS SURVEY No. 12028	on set CATO
D-10 - Estab. ctr of No. 1 - Establish N1/8 N½ cor of S-29. B - Establish N1/8 cor of S-29. B - Estab. W1/8 cor line between W½ D-10 Drove 5/8" x 34" rest ced post w/lost sugar maple for sugar maple for sugar maple sugar maple sugar maple sugar maple sugar maple sugar maple for sugar maple sugar maple sugar maple sugar maple sugar maple for sugar maple sugar maple for sugar maple sugar maple sugar maple sugar maple for sugar maple	of Sec. 29 at Wk of Sec. 29 cor on N-S k I ner on E-Wk I i cor & ctr of of the for corner and ac rod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265' Due N 310' REGISTRATION CD STATES AGEN	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established Dro ced 20 10" 14" E-W Fd NO. 12028 CIES:	Govt lot 9 midway a (NW corne to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir DA	7) per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w c tag N60°W N70°E S35°W South West TE	ion of the corner: 7/R.L.S. cap; 37.2' 30.2' 53.9' 12' 5.6' CARL F. ROSI LAND SURVEY NO. 12026	on set CHICA
D-10 - Estab. ctr of No. 14 - Estab. ctr of No. 15 - Establish N1/8 No. 15 cor of S-29. B - Estab. W1/8 cor of Inne between W2. C. Description of monumer D-10 Drove 5/8" x 34" recomple set ced post w/10 12" sugar maple 6" sugar maple 12" swp oak E edge Mu Rv S edge Mu Rv SIGNED BY SURVEYOR'S MICHIGAN FOR STATE AND UNITE	of Sec. 29 at Wk of Sec. 29 cor on N-S k I ner on E-Wk I i cor & ctr of of the for corner and ac rod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265' Due N 310' REGISTRATION CD STATES AGEN	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established Dro ced 20 10" 14" E-W Fd NO. 12028 CIES:	Govt lot 9 midway a (NW corne to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir DA	7) per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w c tag N60°W N70°E S35°W South West TE	ion of the corner: 7/R.L.S. cap; 37.2' 30.2' 53.9' 12' 5.6' CARL F. ROSI LAND SURVEY NO. 12026	on set CHICA ER OR
D-10 - Estab. ctr of No. 1 - Establish N1/8 N½ cor of S-29. B - Estab. W1/8 cor line between W½ Description of monumer D-10 Drove 5/8" x 34" rest ced post w/lost sugar maple for sugar maple for sugar maple sugar maple sugar maple sugar maple sugar maple for sugar maple sugar maple sugar maple sugar maple for sugar maple sugar	of Sec. 29 at Wk of Sec. 29 cor on N-S k I ner on E-Wk I i cor & ctr of of the for corner and ac rod w/RLS cap c tag N40°W 10.8 S75°E 12.4 S60°W 5.5 Due W 265' Due N 310' REGISTRATION CD STATES AGEN	intersection (NW corner of line of Sec. 29) Ine of Sec. 29 Sec. 29. cessories established Dro ced 20 10" 14" E-W Fd NO. 12028 CIES:	Govt lot 9 midway a (NW corne to perpetuate ve 5/8" x post w/lo Oak oak oak Sand rd Ir DA	7) per std B nd on line b r of Govt Lo locating the posit 4 34" re-rod w c tag N60°W N70°E S35°W South West TE DATE	ion of the corner: 7/R.L.S. cap; 37.2' 30.2' 53.9' 12' 5.6' CARL F. ROSI LAND SURVEY NO. 12026	on set CA CA CA CA CA CA CA CA CA CA CA CA CA