LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. S., R. 6 E. W.	A-12; B-12;
2. PROPERTY CONTROLLING IN SECTION ____	,T. ____ N. S., R. ____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION 31	,T. 19 N. S., R. 6 E. W.	*350' S of B-12

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 2/4; 2/6; 2/4, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Feb 4, 1985, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED

*350'S of B-12

Fd 1" pipe w/RLS cap; added ced post w/loc tag

33"	Maple	N75°E	11.8'
12"	Maple	S60°E	11.0'
19"	Maple in clump 3	S30°W	26.0'
S'ly edge riv		Due N	2'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-12 - Fd & accepted Osceola Co. Mon for W¼ cor; Sec. 31

B-12 - Estab ctr of Sec. 31 at intersection of ¼ lines.

350' S of B-12 - Fd & accepted 1" pipe (M.C.) by RLS Matt McClung, on N-S¼ line, south side of Muskegon Rv, Sec. 31; (NE cor of Govt. Lot 3). Pipe is S01°43'23"E 350.17' from calc. ctr of Sec. 31.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-12

Fd. Osceola Co. Mon; added ced post

20"	R Oak	N05°W	28.61'
14"	W oak in clump	N45°E	15.80'
22"	R oak	S45°E	3.20'
12"	R pine	S35°W	93.55'
ctr dirt rd W'ly		Due S	18' ±
ctr dirt rd S'ly		Due W	15' ±

B-12

Drove 5/8" x 34" rerod w/RLS cap; set ced post w/loc tag

7"	Maple	N5°W	26.1'
10"	Ash	S40°E	41.0'
10"	Ash	S10°W	33.4'
N'ly edge Mu. Rv.		Due S	127'

SIGNED BY Carl F. Roser 01-06-86 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

REDDING TWP
CLARE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET