LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	
2. PROPERTY CONTROLLING IN SECTION 31	,T. 19 N. S., R. 6 E. W.	12 ; 14
3. MISCELLANEOUS PROPERTY IN SECTION 31	,T. 19 N. S., R. 6 E. W.	*1183' W of code -12

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 2/4; 1/31; 2/6, 19 85, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Jan. 31, 19 85, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

~~[illegible]~~

14
Drive 5/8" x 34" rerod w/RLS cap &
set ced post w/loc tag

3" Maple & old		
34" W. Pine stp	N05°E	26.1'
8" Balsam	S80°E	38.8'
6" B. Cherry	S25°E	20.5'
8" Maple	N85°W	25.0'
Skidding trail NW & SE	Due S	17'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

12 - Fd and accepted 1" pipe by R.L.S., Matt McClung, for NE cor of Govt Lot 10 (NW cor of S½ of SE¼), Sec. 31

1183' W of Code 12 - Fd 5/8" rod by R.L.S., M. McClung, on N line of Govt. Lot 10 (S. line of G.L. 3) on east side of Muskegon Rv. Fd pinch pipe, S30°W, 49.1' was probably by R. McCall, "Hunters River Have", April 1957 (this point not accepted to control N line of Govt Lot 10, this survey).

14 - Estab. S 1/8 cor on E line of S-31 per std B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

12
Fd 1" pipe w/RLS cap; added ced post w/loc tag

4" Maple	N60°W	28.7'
5" Basswood	N05°E	17.0'
4" Ash	S55°E	27.0'
12" Cedar	S45°W	12.1'

1183' W of Code 12
Fd 5/8" iron rod w/RLS cap 13037; added ced post

12" ced	N20°W	14.5'
4" sugar maple	S85°E	14.1'
5" sugar maple	S10°E	20.0'
Ely edge Mu rv	Due W	106± 3'
Fd pinch pipe	S30°W	40.1'

SIGNED BY Carl F. Roser 01-06-86 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

REDDING TWP.
CLARE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET