LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	_____
2. PROPERTY CONTROLLING IN SECTION 31	,T. 19 N. S., R. 6 E. W.	15
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	_____

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 14, 1984, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

15 - Established the west 1/16 corner on S line of Sec. 31 (NW cor of E½of NW¼ of Sec. 6, T18N-R6W) on line between the S¼ cor and SW cor (in Rv.) of Sec. 31 and at prorated distance to G.L.O. (U.S.) survey. The reason for setting this 1/16 cor was to have a meaningful point on the south line of Sec. 31 between the Rv & the S ¼ cor of S-31. The state owns Govt. Lot 10 (among other ownership) in S-31 which means state title carries west of the 1/16 cor to the river along the south line of Sec. 31. NOTE: Fd 2" leaning yellow pipe, S76°08'W, 135.0' from said NW corner of E½ of NW¼ of Sec. 6, T18N-R6W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

15
Set 5/8" x 34" rerod w/RLS cap & ced post
w/loc tag

21" R oak (in clump 3)	N05°W	5.6'
3" W pine	S85°E	44.7'
21" R pine	S45°W	37.0'
ctr power line WNW&ESE	Due S	73'
ctr E-W trail	Due S	31'
SEly edge Mu. Rv.	Due W	214'±2'

SIGNED BY Carl F. Roser 01-06-86 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

REDDING TWP.
CLARE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

Reproduced by the State of Michigan